

BERTI CKT/SB HYDRAULIC MULCHER - MINI EXCAVATOR



Hydraulic Mulching Head to Suit Mini Excavators

Suitable for mini excavators from 3.5 to 5.5 tons. Ideal for mulching grass, branches, scrub and vegetation up to Ø 40mm. Compact and high performing, it can be used for several purposes such as pre-construction clearing, public and private green maintenance and agriculture.

PRODUCT DETAILS

Make	Berti
Model	CKT/SB100, CKT/SB80
Weight	235kg, 265kg
Excavator weight	3.5-5.5 ton
Cutting Width	1000mm, 800mm
Dimensions	1150 x 840 x 58mm, 950 x 840 x 580mm
SKU	BERTI-CKT-SB

DISCLAIMER

The material and information contained on this website is for general information purposes only. You should not rely upon the material or information on the website as a basis for making business, legal, or any other decisions. Whilst we endeavour to keep the information up to date and correct, Agpower makes no representations or warranties of any kind, express or implied about the completeness, accuracy, reliability, suitability, or availability with respect to the website or the information, products, services, or related graphics contained on the website for any purpose. Any reliance you place on such material is therefore strictly at your own risk.

CONTACT DETAILS

New & Used Machinery: Brad Storey | Mobile: 0409 138 830 | Email: administration@agpower.com.au

Spare Parts & Accessories: Trevor Phelan | Mobile: 0458 036 370 | Email: administration@agpower.com.au

Agpower & Transport Pty Ltd

465 Maroondah Highway,
Lilydale Vic 3140

Phone: (03) 9739 5006
Fax: (03) 9739 5187

[/agpowerLilydale](https://www.facebook.com/agpowerLilydale)
[/agpower_and_transport_lilydale](https://www.instagram.com/agpower_and_transport_lilydale)



(03) 9739 5006  465 MAROONDAH HWY, LILYDALE VIC 3140

PRODUCT DESCRIPTION

Standard Features

- Double plate main body.
- Multi belt side transmission.
- Height adjustable levelling roller.
- Side skids with replaceable wear shoes.
- Helical flail rotor design.
- Forged and hardened hammers type "B".
- Counter blades.
- Protective cover for motor.
- Hydraulic gear motor with case drainage line.
- Hydraulic valve block, "Berti Fluid Box" (max 120 l/min).
- Hydraulic hoses (L= 2m) with hose burst protection sheaths (excluding QR couplings).
- Self-levelling support with mounting hitch with pins.
- Accident prevention and protection guards to EC directives.

DISCLAIMER

The material and information contained on this website is for general information purposes only. You should not rely upon the material or information on the website as a basis for making business, legal, or any other decisions. Whilst we endeavour to keep the information up to date and correct, Agpower makes no representations or warranties of any kind, express or implied about the completeness, accuracy, reliability, suitability, or availability with respect to the website or the information, products, services, or related graphics contained on the website for any purpose. Any reliance you place on such material is therefore strictly at your own risk.

CONTACT DETAILS

New & Used Machinery: Brad Storey | Mobile: 0409 138 830 | Email: administration@agpower.com.au

Spare Parts & Accessories: Trevor Phelan | Mobile: 0458 036 370 | Email: administration@agpower.com.au

Agpower & Transport Pty Ltd

 465 Maroondah Highway,
Lilydale Vic 3140

 Phone: (03) 9739 5006
 Fax: (03) 9739 5187

 /agpowerLilydale
 /agpower_and_transport_lilydale