

BERTI ECF/MD MULCHER - MEDIUM DUTY



Medium Duty Forestry Mulcher Equipped with Single Edge 360° Swinging Hammers.

Suitable for tractors from 80 to 130hp. Ideal for mulching uncultivated vegetation, scrub, gorse trees, branches and tree trunks up to Ø 150mm.

PRODUCT DETAILS

Make	Berti
Model	ECF/MD140, ECF/MD160, ECF/MD180, ECF/MD200, ECF/MD220
Weight	1420kg, 1450kg, 1495kg, 1530kg, 1570kg
Tractor HP	80-130hp
Cutting Width	1400mm, 1600mm, 1800mm, 2000mm, 2200mm
Dimensions	1750 x 1300 x 1200mm, 1950 x 1300 x 1200mm, 2150 x 1300 x 1200mm, 2350 x 1300 x 1200mm, 2550 x 1300 x 1200mm
Tractor CAT Connection	3-point linkage., Fixed Cat. II
SKU	BERTI-ECF-MD

DISCLAIMER

The material and information contained on this website is for general information purposes only. You should not rely upon the material or information on the website as a basis for making business, legal, or any other decisions. Whilst we endeavour to keep the information up to date and correct, Agpower makes no representations or warranties of any kind, express or implied about the completeness, accuracy, reliability, suitability, or availability with respect to the website or the information, products, services, or related graphics contained on the website for any purpose. Any reliance you place on such material is therefore strictly at your own risk.

CONTACT DETAILS

New & Used Machinery: Brad Storey | Mobile: 0409 138 830 | Email: administration@agpower.com.au

Spare Parts & Accessories: Trevor Phelan | Mobile: 0458 036 370 | Email: administration@agpower.com.au

Agpower & Transport Pty Ltd

📍 465 Maroondah Highway,
Lilydale Vic 3140

☎ Phone: (03) 9739 5006
📠 Fax: (03) 9739 5187

📘 /agpowerLilydale
📷 /agpower_and_transport_lilydale



(03) 9739 5006  465 MAROONDAH HWY, LILYDALE VIC 3140

PRODUCT DESCRIPTION

Standard Features

- Fixed Cat. II, 3-point linkage.
- Hydraulic adjustable rear hood.
- Half-moon skids with replaceable wear shoes.
- Freewheel in the gearbox.
- Double skin body.
- Rotor Ø 440mm with hammers.
- Counter-blades.
- Single edged 360° swinging BERTI hammers.
- PTO 540 rpm (1000 rpm indent).
- Heavy duty PTO driveshaft (1"3/8 6 spline).
- Accident prevention and protection guards to EC directives.

* If for front tractor linkage use, P.O.A.

Options

- Protective arch with mechanical adjustment.
- Centrifugal clutch, exclusive design by BERTI.
- Single edge hammers with tungsten tips (in lieu of standard).

DISCLAIMER

The material and information contained on this website is for general information purposes only. You should not rely upon the material or information on the website as a basis for making business, legal, or any other decisions. Whilst we endeavour to keep the information up to date and correct, Agpower makes no representations or warranties of any kind, express or implied about the completeness, accuracy, reliability, suitability, or availability with respect to the website or the information, products, services, or related graphics contained on the website for any purpose. Any reliance you place on such material is therefore strictly at your own risk.

CONTACT DETAILS



New & Used Machinery: Brad Storey | Mobile: 0409 138 830 | Email: administration@agpower.com.au

Spare Parts & Accessories: Trevor Phelan | Mobile: 0458 036 370 | Email: administration@agpower.com.au

Agpower & Transport Pty Ltd

 465 Maroondah Highway,
Lilydale Vic 3140

 Phone: (03) 9739 5006
 Fax: (03) 9739 5187

 /agpowerLilydale
 /agpower_and_transport_lilydale