

BERTI ECF MULCHER - HEAVY DUTY



Heavy Duty Forestry Mulcher Equipped with Single Edge 360° Swinging Hammers.

Suitable for tractors from 110 to 200hp. It is ideal for mulching uncultivated vegetation, scrub, gorse trees, branches and tree trunks up to Ø 250mm.

PRODUCT DETAILS

Make	Berti
Model	ECF180, ECF200, ECF220
Weight	1620kg, 1725kg, 1860kg
Tractor HP	110-200hp
Cutting Width	1800mm, 2000mm, 2200mm
Dimensions	2130 x 1300 x 1050mm, 2330 x 1300 x 1050mm, 2530 x 1300 x 1050mm
Tractor CAT Connection	3-point linkage., Fixed Cat. II

DISCLAIMER

The material and information contained on this website is for general information purposes only. You should not rely upon the material or information on the website as a basis for making business, legal, or any other decisions. Whilst we endeavour to keep the information up to date and correct, Agpower makes no representations or warranties of any kind, express or implied about the completeness, accuracy, reliability, suitability, or availability with respect to the website or the information, products, services, or related graphics contained on the website for any purpose. Any reliance you place on such material is therefore strictly at your own risk.

CONTACT DETAILS

New & Used Machinery: Brad Storey | Mobile: 0409 138 830 | Email: administration@agpower.com.au

Spare Parts & Accessories: Trevor Phelan | Mobile: 0458 036 370 | Email: administration@agpower.com.au

Agpower & Transport Pty Ltd

📍 465 Maroondah Highway,
Lilydale Vic 3140

☎ Phone: (03) 9739 5006
📠 Fax: (03) 9739 5187

📘 /agpowerLilydale
📷 /agpower_and_transport_lilydale



(03) 9739 5006 📞 465 MAROONDAH HWY, LILYDALE VIC 3140

SKU

BERTI-ECF

PRODUCT DESCRIPTION

Standard Features

- Fixed Cat. II, 3-point linkage.
 - Hydraulic adjustable rear hood.
 - Adjustable half-moon skids with replaceable wear shoes.
 - Gearbox with 1"3/4 input shaft.
 - Free wheel in the PTO drive shaft.
 - Double skin body.
 - Rotor Ø 520mm with hammers.
 - Counter-blades.
 - Single edged 360° swinging BERTI hammers.
 - PTO 1000 rpm.
 - Heavy duty PTO driveshaft (1"3/8 21 spline).
 - Accident prevention and protection guards to EC directives.
- * If for front tractor linkage use, P.O.A.

Options

- Protective arch with mechanical adjustment.
- Centrifugal clutch, exclusive design by BERTI.
- Single edge hammers with tungsten tips (in lieu of standard).

DISCLAIMER

The material and information contained on this website is for general information purposes only. You should not rely upon the material or information on the website as a basis for making business, legal, or any other decisions. Whilst we endeavour to keep the information up to date and correct, Agpower makes no representations or warranties of any kind, express or implied about the completeness, accuracy, reliability, suitability, or availability with respect to the website or the information, products, services, or related graphics contained on the website for any purpose. Any reliance you place on such material is therefore strictly at your own risk.

CONTACT DETAILS

New & Used Machinery: Brad Storey | Mobile: 0409 138 830 | Email: administration@agpower.com.au

Spare Parts & Accessories: Trevor Phelan | Mobile: 0458 036 370 | Email: administration@agpower.com.au

Agpower & Transport Pty Ltd

📍 465 Maroondah Highway,
Lilydale Vic 3140

📞 Phone: (03) 9739 5006
📠 Fax: (03) 9739 5187

📘 /agpowerLilydale
📷 /agpower_and_transport_lilydale