

BERTI LAND MULCHER - HIGH BODY



Universal High Body Mulcher.

Suitable for tractors from 50 to 140hp. Ideal for mulching grass, maize stalks, vegetable topping, sugar cane, potatoes and pasture topping applications.

PRODUCT DETAILS

Make	Berti
Model	LAND 160, LAND 180, LAND 200, LAND 230, LAND 250, LAND 285, LAND 300
Weight	1035kg, 1085kg, 1125kg, 1230kg, 1300kg, 1415kg, 1445kg
Tractor HP	50-140hp
Cutting Width	1600mm, 1800mm, 2000mm, 2300mm, 2500mm, 2850mm, 3000mm
Dimensions	1780 x 1550 x 1050mm, 1980 x 1550 x 1050mm, 2180 x 1550 x 1050mm, 2480 x 1550 x 1100mm, 2680 x 1550 x 1100mm, 3030 x 1550 x 1100mm, 3180 x 1550 x 1100mm
Tractor CAT Connection	3-point linkage., Fixed Cat. I-II
SKU	BERTI-LAND

PRODUCT DESCRIPTION

Standard Features

- Fixed Cat. I-II, 3-point linkage.

DISCLAIMER

The material and information contained on this website is for general information purposes only. You should not rely upon the material or information on the website as a basis for making business, legal, or any other decisions. Whilst we endeavour to keep the information up to date and correct, Agpower makes no representations or warranties of any kind, express or implied about the completeness, accuracy, reliability, suitability, or availability with respect to the website or the information, products, services, or related graphics contained on the website for any purpose. Any reliance you place on such material is therefore strictly at your own risk.

CONTACT DETAILS

New & Used Machinery: Brad Storey | Mobile: 0409 138 830 | Email: administration@agpower.com.au

Spare Parts & Accessories: Trevor Phelan | Mobile: 0458 036 370 | Email: administration@agpower.com.au

Agpower & Transport Pty Ltd

📍 465 Maroondah Highway,
Lilydale Vic 3140

📞 Phone: (03) 9739 5006
📠 Fax: (03) 9739 5187

📘 /agpowerLilydale
📷 /agpower_and_transport_lilydale



(03) 9739 5006  465 MAROONDAH HWY, LILYDALE VIC 3140

- Rear adjustable discharge.
- Free wheel in the gearbox.
- Double skin body.
- Fully automatic belt tensioner.
- Height adjustable levelling roller Ø 194mm with scraper.
- BERTI heavy duty 10mm "Y" flail.
- Counter-blades forged, bolted.
- PTO 540 rpm (TSB 160-250).
- PTO 1000 rpm (TSB 270-300).
- Heavy duty PTO driveshaft (1"3/8 6 spline).
- Accident prevention and protection guards to EC directives.

Options

- Skids
- "T" hammers (in lieu of "Y" blades, factory fit only).
- Hydraulic side shift (LAND/S (indent only)).
- 2 steering wheels TSB250-300 (in lieu of roller).

DISCLAIMER

The material and information contained on this website is for general information purposes only. You should not rely upon the material or information on the website as a basis for making business, legal, or any other decisions. Whilst we endeavour to keep the information up to date and correct, Agpower makes no representations or warranties of any kind, express or implied about the completeness, accuracy, reliability, suitability, or availability with respect to the website or the information, products, services, or related graphics contained on the website for any purpose. Any reliance you place on such material is therefore strictly at your own risk.

CONTACT DETAILS

New & Used Machinery: Brad Storey | Mobile: 0409 138 830 | Email: administration@agpower.com.au

Spare Parts & Accessories: Trevor Phelan | Mobile: 0458 036 370 | Email: administration@agpower.com.au

Agpower & Transport Pty Ltd

 465 Maroondah Highway,
Lilydale Vic 3140

 Phone: (03) 9739 5006
 Fax: (03) 9739 5187

 /agpowerLilydale
 /agpower_and_transport_lilydale