

BERTI TA/PF MULCHER - LOW SWING ARM - HEAVY DUTY



Heavy Duty Offset/In-line Mulcher for Grass, Vegetation and Branches.

Suitable for tractors from 85 to 180 hp. Ideal machine for farmers and contractors who need to mulch prunings in orchards, slopes, ditches and banks of watercourses up to Ø 8 cm.

PRODUCT DETAILS

Make	Berti
Model	TA/PF160, TA/PF180, TA/PF200, TA/PF220, TA/PF250
Weight	1100kg, 1150kg, 1210kg, 1320kg, 940kg
Tractor HP	85-180hp
Cutting Width	1600mm, 1800mm, 2000mm, 2200mm, 2500mm
Dimensions	-
Tractor CAT Connection	3-point linkage hitch with safety lock., Floating/fixed Cat. II

DISCLAIMER

The material and information contained on this website is for general information purposes only. You should not rely upon the material or information on the website as a basis for making business, legal, or any other decisions. Whilst we endeavour to keep the information up to date and correct, Agpower makes no representations or warranties of any kind, express or implied about the completeness, accuracy, reliability, suitability, or availability with respect to the website or the information, products, services, or related graphics contained on the website for any purpose. Any reliance you place on such material is therefore strictly at your own risk.

CONTACT DETAILS

New & Used Machinery: Brad Storey | Mobile: 0409 138 830 | Email: administration@agpower.com.au

Spare Parts & Accessories: Trevor Phelan | Mobile: 0458 036 370 | Email: administration@agpower.com.au

Agpower & Transport Pty Ltd

📍 465 Maroondah Highway,
Lilydale Vic 3140

☎ Phone: (03) 9739 5006
📠 Fax: (03) 9739 5187

📘 /agpowerLilydale
📷 /agpower_and_transport_lilydale

(03) 9739 5006  465 MAROONDAH HWY, LILYDALE VIC 3140

SKU

BERTI-TA-PF

PRODUCT DESCRIPTION

Standard Features

- Floating/fixed Cat II 3-point linkage hitch with safety lock.
 - Rear adjustable discharge hood.
 - Chamfered body profile RHS front corner.
 - Full automatic belt tensioner.
 - Free wheel in the gearbox.
 - Hydraulic side shift with breakaway valve.
 - Hydraulic cylinder for head positioning with floating link and safety valve.
 - Height adjustable levelling roller 159 mm with scraper.
 - Counter-blades forged.
 - Collecting rakes.
 - Double skin body.
 - Heavy duty rotor.
 - Forged and hardened BERTI 1.9 kg hammers type "A".
 - PTO 540 rpm.
 - Heavy duty hardened double wide angle PTO driveshaft (1"3/8 6 spline).
 - Accident prevention & protection guards to EC directives.
- * The tractor has to be equipped with 2 double acting remotes.

Options

- Skids.

DISCLAIMER


The material and information contained on this website is for general information purposes only. You should not rely upon the material or information on the website as a basis for making business, legal, or any other decisions. Whilst we endeavour to keep the information up to date and correct, Agpower makes no representations or warranties of any kind, express or implied about the completeness, accuracy, reliability, suitability, or availability with respect to the website or the information, products, services, or related graphics contained on the website for any purpose. Any reliance you place on such material is therefore strictly at your own risk.



CONTACT DETAILS



New & Used Machinery: Brad Storey | Mobile: 0409 138 830 | Email: administration@agpower.com.au

Spare Parts & Accessories: Trevor Phelan | Mobile: 0458 036 370 | Email: administration@agpower.com.au

Agpower & Transport Pty Ltd

 465 Maroondah Highway,
Lilydale Vic 3140

 Phone: (03) 9739 5006
 Fax: (03) 9739 5187

 /agpowerLilydale
 /agpower_and_transport_lilydale