

BERTI XPRO MULCHER - EXTRA HEAVY DUTY



Extra Heavy Duty Professional Mulcher to Fit Front and Rear Tractor Linkage or Reverse Drive Tractors.

Suitable for tractors from 100 to 250hp. It is suited for mulching grass, heavy vegetation, undergrowth, scrub, prunings and branches up to Ø 80-100mm (XPRO/F Ø 100-120mm). Ideal for heavy field, orchard, vegetable topping and roadside applications.

PRODUCT DETAILS

Make	Berti
Model	XPRO200, XPRO230, XPRO250, XPRO285, XPRO300
Weight	1555kg, 1645kg, 1705kg, 1810kg, 1850kg
Tractor HP	100-250hp
Cutting Width	2000mm, 2300mm, 2500mm, 2850mm, 3000mm
Dimensions	2200 x 1370 x 1220mm, 2500 x 1370 x 1220mm, 2700 x 1370 x 1220mm, 3050 x 1370 x 1220mm, 3200 x 1370 x 1220mm
Tractor CAT Connection	center mounted Cat. II-III 3-point linkage., Double sided
SKU	BERTI-XPRO

PRODUCT DESCRIPTION

Standard Features

DISCLAIMER


The material and information contained on this website is for general information purposes only. You should not rely upon the material or information on the website as a basis for making business, legal, or any other decisions. Whilst we endeavour to keep the information up to date and correct, Agpower makes no representations or warranties of any kind, express or implied about the completeness, accuracy, reliability, suitability, or availability with respect to the website or the information, products, services, or related graphics contained on the website for any purpose. Any reliance you place on such material is therefore strictly at your own risk.



CONTACT DETAILS



New & Used Machinery: Brad Storey | Mobile: 0409 138 830 | Email: administration@agpower.com.au

Spare Parts & Accessories: Trevor Phelan | Mobile: 0458 036 370 | Email: administration@agpower.com.au

Agpower & Transport Pty Ltd

 465 Maroondah Highway,
Lilydale Vic 3140

 Phone: (03) 9739 5006
 Fax: (03) 9739 5187

 /agpowerLilydale
 /agpower_and_transport_lilydale



(03) 9739 5006  465 MAROONDAH HWY, LILYDALE VIC 3140

- Double sided, center mounted Cat. II-III 3-point linkage.
- Hydraulic side shift.
- Rear adjustable discharge hood.
- Full automatic belt tensioner.
- Double free wheel and 1³/₄ through shaft in the gearbox.
- Height adjustable self-cleaning levelling roller Ø 220.
- Double skin body, inner skin Strenx steel.
- Heavy-duty rotor.
- Skids.
- Counter-blades forged, bolted.
- Front protection chains with rubber.
- Forged and hardened BERTI 2.4kg hammers type "M".
- PTO 1000 rpm (540 rpm optional).
- Heavy duty PTO driveshaft (1³/₈ 6 spline).
- Accident prevention and protection guards to EC directives.

Options

- Weight relief springs (front mounting).
- Front pivot wheel kit (indent only).

DISCLAIMER

The material and information contained on this website is for general information purposes only. You should not rely upon the material or information on the website as a basis for making business, legal, or any other decisions. Whilst we endeavour to keep the information up to date and correct, Agpower makes no representations or warranties of any kind, express or implied about the completeness, accuracy, reliability, suitability, or availability with respect to the website or the information, products, services, or related graphics contained on the website for any purpose. Any reliance you place on such material is therefore strictly at your own risk.

CONTACT DETAILS

New & Used Machinery: Brad Storey | Mobile: 0409 138 830 | Email: administration@agpower.com.au

Spare Parts & Accessories: Trevor Phelan | Mobile: 0458 036 370 | Email: administration@agpower.com.au

Agpower & Transport Pty Ltd

 465 Maroondah Highway,
Lilydale Vic 3140

 Phone: (03) 9739 5006
 Fax: (03) 9739 5187

 /agpowerLilydale
 /agpower_and_transport_lilydale