

CELLI POWER HARROW - GO



TRACTORS FROM 40 - 100 HP

Light duty power harrow for tractors up to 80 / 100 hp. Suitable for small agricultural applications.

PRODUCT DETAILS

Make	Celli
Model	GO 150, GO 175, GO 200, GO 225, GO 250, GO 300
Working Width	1500mm, 1750mm, 2000mm, 2250mm, 2500mm, 3000mm
Tractor HP	100hp (max)
Weight	570kg, 630kg, 690kg, 750kg, 810kg, 910kg
Overall Width	1550mm, 1800mm, 2050mm, 2250mm, 2500mm, 3000mm
SKU	CELLI-13

PRODUCT DESCRIPTION

TECHNICAL SPECIFICATIONS

DISCLAIMER


The material and information contained on this website is for general information purposes only. You should not rely upon the material or information on the website as a basis for making business, legal, or any other decisions. Whilst we endeavour to keep the information up to date and correct, Agpower makes no representations or warranties of any kind, express or implied about the completeness, accuracy, reliability, suitability, or availability with respect to the website or the information, products, services, or related graphics contained on the website for any purpose. Any reliance you place on such material is therefore strictly at your own risk.

CONTACT DETAILS



New & Used Machinery: Brad Storey | Mobile: 0409 138 830 | Email: administration@agpower.com.au

Spare Parts & Accessories: Trevor Phelan | Mobile: 0458 036 370 | Email: administration@agpower.com.au

Agpower & Transport Pty Ltd

 465 Maroondah Highway,
Lilydale Vic 3140

 Phone: (03) 9739 5006
 Fax: (03) 9739 5187

 /agpowerLilydale
 /agpower_and_transport_lilydale



(03) 9739 5006  465 MAROONDAH HWY, LILYDALE VIC 3140

- Fully welded geared to give greater rigidity and ensure gears stay “true at all times”
- 15 degree rotor time to reduce horsepower demand and fuel consumption, producing a finer seedbed
- Boron steel tines
- Forged and heat treated one piece rotor shafts
- Greasable top bearings to ensure they have adequate lubrication
- 45 degree moving side plates to ensure flat finish for seedbed preparation
- Hardened gears for long life
- Rear levelling bar with pin height adjustment
- Manual depth control
- Shearbolt clutch

DISCLAIMER

The material and information contained on this website is for general information purposes only. You should not rely upon the material or information on the website as a basis for making business, legal, or any other decisions. Whilst we endeavour to keep the information up to date and correct, Agpower makes no representations or warranties of any kind, express or implied about the completeness, accuracy, reliability, suitability, or availability with respect to the website or the information, products, services, or related graphics contained on the website for any purpose. Any reliance you place on such material is therefore strictly at your own risk.

CONTACT DETAILS

New & Used Machinery: Brad Storey | Mobile: 0409 138 830 | Email: administration@agpower.com.au

Spare Parts & Accessories: Trevor Phelan | Mobile: 0458 036 370 | Email: administration@agpower.com.au

Agpower & Transport Pty Ltd

 465 Maroondah Highway,
Lilydale Vic 3140

 Phone: (03) 9739 5006
 Fax: (03) 9739 5187

 /agpowerLilydale
 /agpower_and_transport_lilydale