

CELLI POWER HARROW - RANGER



TRACTORS FROM 50 - 130 HP

Medium duty power harrow for tractors up to 110 / 130 hp.

Suitable for small agricultural applications

PRODUCT DETAILS

Make	Celli
Model	RANGER 200, RANGER 225, RANGER 250, RANGER 300
Working Width	2000mm, 2250mm, 2500mm, 3000mm
Tractor HP	130hp (max)
Weight	750kg, 830kg, 880kg, 980kg
Overall Width	2050mm, 2300mm, 2550mm, 3050mm
SKU	CELLI-14

PRODUCT DESCRIPTION

TECHNICAL SPECIFICATIONS

- Fully welded geared to give greater rigidity and ensure gears stay “true at all times”

DISCLAIMER

The material and information contained on this website is for general information purposes only. You should not rely upon the material or information on the website as a basis for making business, legal, or any other decisions. Whilst we endeavour to keep the information up to date and correct, Agpower makes no representations or warranties of any kind, express or implied about the completeness, accuracy, reliability, suitability, or availability with respect to the website or the information, products, services, or related graphics contained on the website for any purpose. Any reliance you place on such material is therefore strictly at your own risk.

CONTACT DETAILS

New & Used Machinery: Brad Storey | Mobile: 0409 138 830 | Email: administration@agpower.com.au

Spare Parts & Accessories: Trevor Phelan | Mobile: 0458 036 370 | Email: administration@agpower.com.au

Agpower & Transport Pty Ltd

📍 465 Maroondah Highway,
Lilydale Vic 3140

📞 Phone: (03) 9739 5006
📠 Fax: (03) 9739 5187

📘 /agpowerLilydale
📷 /agpower_and_transport_lilydale



(03) 9739 5006  465 MAROONDAH HWY, LILYDALE VIC 3140

- 15 degree rotor time to reduce horsepower demand and fuel consumption, producing a finer seedbed
- Boron steel tines
- Forged and heat treated one piece rotor shafts
- Greasable top bearings to ensure they have adequate lubrication
- 45 degree moving side plates to ensure flat finish for seedbed preparation
- Hardened gears for long life
- Manual depth control
- Rear levelling bar with winder height control and indicator
- 285mm working depth
- 45 degree sliding side plates
- Shearbolt clutch

DISCLAIMER

The material and information contained on this website is for general information purposes only. You should not rely upon the material or information on the website as a basis for making business, legal, or any other decisions. Whilst we endeavour to keep the information up to date and correct, Agpower makes no representations or warranties of any kind, express or implied about the completeness, accuracy, reliability, suitability, or availability with respect to the website or the information, products, services, or related graphics contained on the website for any purpose. Any reliance you place on such material is therefore strictly at your own risk.

CONTACT DETAILS

New & Used Machinery: Brad Storey | Mobile: 0409 138 830 | Email: administration@agpower.com.au

Spare Parts & Accessories: Trevor Phelan | Mobile: 0458 036 370 | Email: administration@agpower.com.au

Agpower & Transport Pty Ltd

 465 Maroondah Highway,
Lilydale Vic 3140

 Phone: (03) 9739 5006
 Fax: (03) 9739 5187

 /agpowerLilydale
 /agpower_and_transport_lilydale