

# CROPLANDS CROPAIR 1000 TRAILED SPRAYER



The Cropair linkage and trailed range of sprayers are as high quality as they are cost effective, perfect for growers with smaller or boutique operations.

Suits smaller orchards, boutique operations

## PRODUCT DETAILS

<b>Make</b>	Croplands
<b>Model</b>	Cropair 1000
<b>Tank Capacity</b>	1000L
<b>Fan Size</b>	800mm
<b>Pump</b>	130 L/min high pressure (40-bar) diaphragm pump
<b>Power Required</b>	Approximately 50-60 HP required
<b>SKU</b>	CROPLANDS-15

## PRODUCT DESCRIPTION

### DISCLAIMER


The material and information contained on this website is for general information purposes only. You should not rely upon the material or information on the website as a basis for making business, legal, or any other decisions. Whilst we endeavour to keep the information up to date and correct, Agpower makes no representations or warranties of any kind, express or implied about the completeness, accuracy, reliability, suitability, or availability with respect to the website or the information, products, services, or related graphics contained on the website for any purpose. Any reliance you place on such material is therefore strictly at your own risk.



### CONTACT DETAILS

**New & Used Machinery:** Brad Storey | Mobile: 0409 138 830 | Email: [administration@agpower.com.au](mailto:administration@agpower.com.au)

**Spare Parts & Accessories:** Trevor Phelan | Mobile: 0458 036 370 | Email: [administration@agpower.com.au](mailto:administration@agpower.com.au)

### Agpower & Transport Pty Ltd

 465 Maroondah Highway,  
Lilydale Vic 3140

 Phone: (03) 9739 5006  
 Fax: (03) 9739 5187

 /agpowerLilydale  
 /agpower\_and\_transport\_lilydale



(03) 9739 5006  465 MAROONDAH HWY, LILYDALE VIC 3140

#### FAN

- 800mm single speed fan with neutral position.
- Adjustable pitch blades x 9.
- Poly fan cowl.
- Upper deflector kit supplied as standard.

#### DRIVE

- PTO shaft supplied.

#### PUMP

- FM-140, high pressure (40 Bar rated) triple diaphragm pump.
- Open flow output = 130L/min.

#### CONTROLS

- RM-40, 2 x tap remote mounted manual control.
- Manual pressure regulating valve and gauge.
- Optional electric control upgrade.

#### NOZZLES

- 6 x brass rollover nozzle bodies per side.

#### TANK

- High impact, UV-stabilised polyethylene tank fitted with separate flushing and fresh water tanks.

#### CHASSIS / AXLE

- Hot-dipped galvanised chassis with standard draw bar fitted.
- Optional Self-steering drawbar.
- Adjustable width axle fitted with 10.0/80 x 12 implement tyres.

#### POWER REQUIRED

- Recommended tractor engine HP requirement = 50-60 HP.

#### DISCLAIMER


The material and information contained on this website is for general information purposes only. You should not rely upon the material or information on the website as a basis for making business, legal, or any other decisions. Whilst we endeavour to keep the information up to date and correct, Agpower makes no representations or warranties of any kind, express or implied about the completeness, accuracy, reliability, suitability, or availability with respect to the website or the information, products, services, or related graphics contained on the website for any purpose. Any reliance you place on such material is therefore strictly at your own risk.



#### CONTACT DETAILS



**New & Used Machinery:** Brad Storey | Mobile: 0409 138 830 | Email: [administration@agpower.com.au](mailto:administration@agpower.com.au)

**Spare Parts & Accessories:** Trevor Phelan | Mobile: 0458 036 370 | Email: [administration@agpower.com.au](mailto:administration@agpower.com.au)

#### Agpower & Transport Pty Ltd

 465 Maroondah Highway,  
Lilydale Vic 3140

 Phone: (03) 9739 5006  
 Fax: (03) 9739 5187

 /agpowerLilydale  
 /agpower\_and\_transport\_lilydale