

CROPLANDS CROPLINER XL SPRAYER



The perfect solution for operations of all sizes. Multiple tank and fan size combinations can be perfectly matched to your tractor hp and budget requirements.

Suits bush crops, trellis crops, medium size tree crops

PRODUCT DETAILS

Make	Croplands
Model	HTP1500, HTP2000, HTP3000, HTP4000
Tank Capacity	1000L, 2000L, 3000L, 4000L
Fan Size	1060mm, 820mm, 920mm
Pump	AR BHA-140, AR BHS-170
SKU	CROPLANDS-11

PRODUCT DESCRIPTION

TANK

Impact resistant polyethylene tanks with UV-stabilised finish. Calibrated sight gauge, flip-open filling lid with large basket strainer,

DISCLAIMER

The material and information contained on this website is for general information purposes only. You should not rely upon the material or information on the website as a basis for making business, legal, or any other decisions. Whilst we endeavour to keep the information up to date and correct, Agpower makes no representations or warranties of any kind, express or implied about the completeness, accuracy, reliability, suitability, or availability with respect to the website or the information, products, services, or related graphics contained on the website for any purpose. Any reliance you place on such material is therefore strictly at your own risk.

CONTACT DETAILS

New & Used Machinery: Brad Storey | Mobile: 0409 138 830 | Email: administration@agpower.com.au

Spare Parts & Accessories: Trevor Phelan | Mobile: 0458 036 370 | Email: administration@agpower.com.au

Agpower & Transport Pty Ltd

📍 465 Maroondah Highway,
Lilydale Vic 3140

📞 Phone: (03) 9739 5006
📠 Fax: (03) 9739 5187

📘 /agpowerLilydale
📷 /agpower_and_transport_lilydale



(03) 9739 5006  465 MAROONDAH HWY, LILYDALE VIC 3140

separate chemical pre-mixer and 1¼" drain valve. Quick fill system and suction probe fitted standard. Models available:

- 4000 litre main tank with separate 80 litre flush tank
- 3000 litre main tank with separate 90 litre flush tank
- 2000 litre main tank with separate 130 litre flush tank
- 1500 litre main tank with separate 120 litre flush tank Separate 15 litre fresh water tank on 1500 and 2000 litre models.

FAN OPTIONS

- 920mm DSV fan - stainless steel shroud, downstream adjustable straightening vanes, NEW design glassreinforced nylon polymer blades with adjustable pitch, 14 roll-over bodies per side on twin spray rings, 2-speed oil-bath gearbox, centrifugal fan clutch
- 820mm DSV fan - stainless steel shroud, downstream adjustable straightening vanes, NEW design glassreinforced nylon polymer blades with adjustable pitch, 14 roll-over bodies per side on twin spray rings, 2-speed oil-bath gearbox, centrifugal fan clutch
- 820mm Linear Tower - galvanised tower, 7 nozzles per side, 2-speed gearbox, adjustable pitch blades
- 1060mm DSV fan - stainless steel shroud and fixed stainless straightening vanes, NEW design glass-reinforced nylon polymer blades with adjustable pitch, 15 roll-over bodies per side on twin spray rings, 2-speed oil-bath gearbox, centrifugal fan clutch. 1060 fan only available on 3000 and 4000 litre models

PUMP

- 4000, 3000, 2000 litre - AR oil-backed diaphragm type with chemical resistant diaphragms, and corrosion resistant brass heads and manifold (ARBHS170)
- 1500 litre - AR oil-backed diaphragm type with chemical resistant diaphragms, and corrosion resistant cast anodised body (ARBHA140)

DRIVE (SH5AG)

Heavy duty PTO driveshaft comes with safety covers and quick release pins. Optional CV shaft

CONTROLS

Remote mounted ARBMH50 controller with individual left/right shut-off, simultaneous shut-off, full bypass, pressure adjustment and glycerine-filled gauge. Optional electric and auto rate controllers

AGITATION

- 4000, 3000, 2000 litre - twin Supa-flo agitators
- 1500 litre - single Supa-flo agitator

FILTRATION

Lid strainer, large suction filter. Optional pressure filters

NOZZLES

Brass swing-over nozzle bodies, automatic shut-off type.

DISCLAIMER


The material and information contained on this website is for general information purposes only. You should not rely upon the material or information on the website as a basis for making business, legal, or any other decisions. Whilst we endeavour to keep the information up to date and correct, Agpower makes no representations or warranties of any kind, express or implied about the completeness, accuracy, reliability, suitability, or availability with respect to the website or the information, products, services, or related graphics contained on the website for any purpose. Any reliance you place on such material is therefore strictly at your own risk.



CONTACT DETAILS



New & Used Machinery: Brad Storey | Mobile: 0409 138 830 | Email: administration@agpower.com.au

Spare Parts & Accessories: Trevor Phelan | Mobile: 0458 036 370 | Email: administration@agpower.com.au

Agpower & Transport Pty Ltd

 465 Maroondah Highway,
Lilydale Vic 3140

 Phone: (03) 9739 5006
 Fax: (03) 9739 5187

 /agpowerLilydale
 /agpower_and_transport_lilydale



(03) 9739 5006 📞 465 MAROONDAH HWY, LILYDALE VIC 3140

All units supplied with one set of ceramic hollow cone ALBUZ nozzles and one set of disc and core standard.

CHASSIS

- Hot-dipped galvanised, full-length with adjustable
- Drawbar and single step, 6-stud wheel hubs, bumper bar comes with leaf guard. Fixed axle standard; optional adjustable height and width axle.
- Jockey wheel supplied on all models

WHEELS

- 4000, 3000 litre – steel rims, 400 x 15.5" flotation tyres
- 2000, 1500 litre – steel rims, 11.5/80 x 15.3"

POWER REQUIRED

- 920mm DSV fan – minimum 37kW (50 hp) at PTO
- 820mm DSV fan – minimum 34kW (45 hp) at PTO
- 1060mm DSV fan – minimum 71kW (95 hp) at PTO

DISCLAIMER

The material and information contained on this website is for general information purposes only. You should not rely upon the material or information on the website as a basis for making business, legal, or any other decisions. Whilst we endeavour to keep the information up to date and correct, Agpower makes no representations or warranties of any kind, express or implied about the completeness, accuracy, reliability, suitability, or availability with respect to the website or the information, products, services, or related graphics contained on the website for any purpose. Any reliance you place on such material is therefore strictly at your own risk.

CONTACT DETAILS

New & Used Machinery: Brad Storey | Mobile: 0409 138 830 | Email: administration@agpower.com.au

Spare Parts & Accessories: Trevor Phelan | Mobile: 0458 036 370 | Email: administration@agpower.com.au

Agpower & Transport Pty Ltd

📍 465 Maroondah Highway,
Lilydale Vic 3140

📞 Phone: (03) 9739 5006
📠 Fax: (03) 9739 5187

📘 /agpowerLilydale
📷 /agpower_and_transport_lilydale