

## MASCHIO GASPARDO MULCHER - LEOPARD 320DT



The Leopard model is intended for professional use and for those who use the shredder with high-power tractors. The helical layout of the tools on the rotor enhances rotation, thereby reducing vibrations and optimising the cutting quality. It is available with single (ST) or double transmission (DT). The road clearance is less than 3.5m.

### PRODUCT DETAILS

<b>Make</b>	Maschio GasparDo
<b>Model</b>	LEOPARD 320DT
<b>Working Width</b>	3200mm
<b>Overall Width</b>	3490mm
<b>Tractor HP</b>	140-200hp
<b>Weight</b>	-
<b>SKU</b>	MG-LEOPARD-320DT

### PRODUCT DESCRIPTION

- Universal three point fix hitch, cat. II

### DISCLAIMER

The material and information contained on this website is for general information purposes only. You should not rely upon the material or information on the website as a basis for making business, legal, or any other decisions. Whilst we endeavour to keep the information up to date and correct, Agpower makes no representations or warranties of any kind, express or implied about the completeness, accuracy, reliability, suitability, or availability with respect to the website or the information, products, services, or related graphics contained on the website for any purpose. Any reliance you place on such material is therefore strictly at your own risk.

### CONTACT DETAILS

**New & Used Machinery:** Brad Storey | Mobile: 0409 138 830 | Email: [administration@agpower.com.au](mailto:administration@agpower.com.au)

**Spare Parts & Accessories:** Trevor Phelan | Mobile: 0458 036 370 | Email: [administration@agpower.com.au](mailto:administration@agpower.com.au)

### Agpower & Transport Pty Ltd

📍 465 Maroondah Highway,  
Lilydale Vic 3140

☎ Phone: (03) 9739 5006  
📠 Fax: (03) 9739 5187

📘 /agpowerLilydale  
📷 /agpower\_and\_transport\_lilydale



(03) 9739 5006  465 MAROONDAH HWY, LILYDALE VIC 3140

- PTO shaft (1" 3/8 Z6 tractor side yoke)
- 1000 rpm gearbox PTO 1000 rpm for ST and DT versions, with free wheel
- 5 toothed belts single transmission for ST version
- 3+3 belts double transmission with pulleys for DT version
- Blades Kit "05"
- Electronically balanced rotor with 8 rows of helically disposed tools
- Heavy duty barrel type bearings
- Height adjustable Ø 220mm rear levelling roller
- Transmission belts external adjustment
- Lower toothed counter-blade
- Double standing support
- Front safety flaps
- «CE» safety guards

## DISCLAIMER

The material and information contained on this website is for general information purposes only. You should not rely upon the material or information on the website as a basis for making business, legal, or any other decisions. Whilst we endeavour to keep the information up to date and correct, Agpower makes no representations or warranties of any kind, express or implied about the completeness, accuracy, reliability, suitability, or availability with respect to the website or the information, products, services, or related graphics contained on the website for any purpose. Any reliance you place on such material is therefore strictly at your own risk.



## CONTACT DETAILS

**New & Used Machinery:** Brad Storey | Mobile: 0409 138 830 | Email: [administration@agpower.com.au](mailto:administration@agpower.com.au)

**Spare Parts & Accessories:** Trevor Phelan | Mobile: 0458 036 370 | Email: [administration@agpower.com.au](mailto:administration@agpower.com.au)

## Agpower & Transport Pty Ltd

 465 Maroondah Highway,  
Lilydale Vic 3140

 Phone: (03) 9739 5006  
 Fax: (03) 9739 5187

 /agpowerLilydale  
 /agpower\_and\_transport\_lilydale