

MASCHIO GASPARDO ROTARY HOE - SC 250



This Rotary Tiller with multi speed gearbox is designed for large farms and outside contractors. This is a large rotary tiller designed to work in particularly heavy conditions. Its new mechanical structure and wide choice of accessories allow it to achieve excellent results on any type of ground. It is available in the version with Cobra and Condor type blade rotor.

PRODUCT DETAILS

Make	Maschio Gaspardo
Model	SC 250
Working Width	2600mm
Overall Width	2730mm
Tractor HP	100-170hp
Weight	1310kg
SKU	MG-SC-250

PRODUCT DESCRIPTION

- 540/1000 rpm PTO gearbox

DISCLAIMER

The material and information contained on this website is for general information purposes only. You should not rely upon the material or information on the website as a basis for making business, legal, or any other decisions. Whilst we endeavour to keep the information up to date and correct, Agpower makes no representations or warranties of any kind, express or implied about the completeness, accuracy, reliability, suitability, or availability with respect to the website or the information, products, services, or related graphics contained on the website for any purpose. Any reliance you place on such material is therefore strictly at your own risk.

CONTACT DETAILS



New & Used Machinery: Brad Storey | Mobile: 0409 138 830 | Email: administration@agpower.com.au

Spare Parts & Accessories: Trevor Phelan | Mobile: 0458 036 370 | Email: administration@agpower.com.au

Agpower & Transport Pty Ltd

 465 Maroondah Highway,
Lilydale Vic 3140

 Phone: (03) 9739 5006
 Fax: (03) 9739 5187

 /agpowerLilydale
 /agpower_and_transport_lilydale



(03) 9739 5006  465 MAROONDAH HWY, LILYDALE VIC 3140

- Rotor revolutions PTO 540 rpm (3s): 133-162-220
- Rotor revolutions PTO 1000 rpm (3s): 181-246-300
- PTO shaft with slip clutch(1" 3/8 Z6 tractor side yoke)
- Side gears drive in oil bath
- Universal three point hitch, cat. II^
- Swinging front hitches
- Rear PTO
- 6 blades per flange (side blades are always mounted inwards)
- Bonnet spring adjusters
- Pair of skids
- Heavy duty barrel type bearings
- "Duo cone" waterproof sealings, oil bath lubrication
- Third point linkages standard on 280 and wider versions
- «CE» safety guards
- Version with Ø 570 mm rotor available upon request
- Version with outwards mounted side blades available upon request

DISCLAIMER

The material and information contained on this website is for general information purposes only. You should not rely upon the material or information on the website as a basis for making business, legal, or any other decisions. Whilst we endeavour to keep the information up to date and correct, Agpower makes no representations or warranties of any kind, express or implied about the completeness, accuracy, reliability, suitability, or availability with respect to the website or the information, products, services, or related graphics contained on the website for any purpose. Any reliance you place on such material is therefore strictly at your own risk.

CONTACT DETAILS

New & Used Machinery: Brad Storey | Mobile: 0409 138 830 | Email: administration@agpower.com.au

Spare Parts & Accessories: Trevor Phelan | Mobile: 0458 036 370 | Email: administration@agpower.com.au

Agpower & Transport Pty Ltd

 465 Maroondah Highway,
Lilydale Vic 3140

 Phone: (03) 9739 5006
 Fax: (03) 9739 5187

 /agpowerLilydale
 /agpower_and_transport_lilydale