

SILVAN 3000L 3 ROW TURBO SCRAM SPRAYER



3000L TURBO SCRAM TRAILED 3 ROW TRI-WRAP: Includes sprayheads 6 x 320mm fans, Hydraulic drive stainless steel pump, automatic spray rate controller, self contained hydraulic drive system, tandem suspension axle

PRODUCT DETAILS

| | |
|------------------------|------------|
| Make | Silvan |
| Model | STU68HB5S3 |
| Tank Capacity | 3000L |
| Connection Type | Trailed |
| Pump | 350L/min |
| Dimensions | - |
| Weight | - |

DISCLAIMER

The material and information contained on this website is for general information purposes only. You should not rely upon the material or information on the website as a basis for making business, legal, or any other decisions. Whilst we endeavour to keep the information up to date and correct, Agpower makes no representations or warranties of any kind, express or implied about the completeness, accuracy, reliability, suitability, or availability with respect to the website or the information, products, services, or related graphics contained on the website for any purpose. Any reliance you place on such material is therefore strictly at your own risk.

CONTACT DETAILS



New & Used Machinery: Brad Storey | Mobile: 0409 138 830 | Email: administration@agpower.com.au

Spare Parts & Accessories: Trevor Phelan | Mobile: 0458 036 370 | Email: administration@agpower.com.au

Agpower & Transport Pty Ltd

 465 Maroondah Highway,
Lilydale Vic 3140

 Phone: (03) 9739 5006
 Fax: (03) 9739 5187

 /agpowerLilydale
 /agpower_and_transport_lilydale



(03) 9739 5006  465 MAROONDAH HWY, LILYDALE VIC 3140

| | |
|------------------------|-------------------|
| Min. PTO Output | 80hp |
| SKU | SILVAN-STU68HB5S3 |

PRODUCT DESCRIPTION

Pump: Stainless steel, hydraulic drive centrifugal pump, 350 L/min. Stainless steel shaft and Viton/ceramic seal. Driven by tractor remotes.

Fan Size: 320 mm turbine fan, one per air tube, 3600 rpm. Power consumed 29 kw / 38HP.

Nozzles: Air shear

Control: Electric section valves with Bravo 180S automatic rate controller. Large 100mm pressure gauge.

Frame: Galvanised steel chassis, linkage hitch fitted with hydraulic power pack.

Tank: Polytuff impact resistant polyethylene construction, calibrated sight line, flip top easy open lid, 50mm camlock bottom fill and hand wash tank. (205L flush tank on 3000L)

Head: Three row spraying head: 42 venturi air shear adjustable nozzles with individual metering and on/off taps. Left & right arms are independent hydraulic folding with adjustable width & centre frame. Boom frame is galvanised.

Filtration: Lid strainer and large capacity suction filter.

Wheel Equipment: Tandem suspension axle with 10 x 15" tyres (3000L)

PTO Drive Shaft: Quality Bondioli & Pavesi driveshaft with quick release pins & safety cover.

DISCLAIMER


The material and information contained on this website is for general information purposes only. You should not rely upon the material or information on the website as a basis for making business, legal, or any other decisions. Whilst we endeavour to keep the information up to date and correct, Agpower makes no representations or warranties of any kind, express or implied about the completeness, accuracy, reliability, suitability, or availability with respect to the website or the information, products, services, or related graphics contained on the website for any purpose. Any reliance you place on such material is therefore strictly at your own risk.



CONTACT DETAILS



New & Used Machinery: Brad Storey | Mobile: 0409 138 830 | Email: administration@agpower.com.au

Spare Parts & Accessories: Trevor Phelan | Mobile: 0458 036 370 | Email: administration@agpower.com.au

Agpower & Transport Pty Ltd

 465 Maroondah Highway,
Lilydale Vic 3140

 Phone: (03) 9739 5006
 Fax: (03) 9739 5187

 /agpowerLilydale
 /agpower_and_transport_lilydale