

SILVAN 600L SILVAN HONDA DAVEY FIRE FIGHTING UNIT



Silvan Fire fighting units are made of high quality components sourced from world class manufacturers. Ideal for water transfer and wash down of machinery, they fit neatly across the back of a one tonne tray and between the wheel arches of popular utilities. All units are fully assembled and tested ready for use.

PRODUCT DETAILS

Make	Silvan
Model	SQF600D
Dimensions	840 x 940 x 1830mm
Pump	425L/min
Max. Pressure	80psi
Tank Capacity	600L
Weight	67kg
SKU	SILVAN-SQF600D

DISCLAIMER

The material and information contained on this website is for general information purposes only. You should not rely upon the material or information on the website as a basis for making business, legal, or any other decisions. Whilst we endeavour to keep the information up to date and correct, Agpower makes no representations or warranties of any kind, express or implied about the completeness, accuracy, reliability, suitability, or availability with respect to the website or the information, products, services, or related graphics contained on the website for any purpose. Any reliance you place on such material is therefore strictly at your own risk.

CONTACT DETAILS

New & Used Machinery: Brad Storey | Mobile: 0409 138 830 | Email: administration@agpower.com.au

Spare Parts & Accessories: Trevor Phelan | Mobile: 0458 036 370 | Email: administration@agpower.com.au

Agpower & Transport Pty Ltd

📍 465 Maroondah Highway,
Lilydale Vic 3140

☎ Phone: (03) 9739 5006
📠 Fax: (03) 9739 5187

📘 /agpowerLilydale
📷 /agpower_and_transport_lilydale



(03) 9739 5006  465 MAROONDAH HWY, LILYDALE VIC 3140

PRODUCT DESCRIPTION

HOSE: 20mtr 3/4" I.D. hose and poly adjustable fire fighter nozzle,
ENGINE: 4 Stroke 5.5HP GX160 Honda Engine, direct coupled Impellor,
INLET & OUTLET DETAILS: Inlet 1 x 1.5", Outlet 1 x 1.5" & 2 x 1",
MAXIMUM HEAD: 56 (metres),
FUEL CAPACITY: 3.6 Litre (Unleaded), 2 hours approx run time,
TANK: UV stabilised Polytuff tank that meets the harsh Australian conditions,
INTERNAL BAFFLE: Internal Baffle to reduce surge when travelling,
TIE DOWN POINTS: Tie down points moulded into the top of the tank,
SCREW DOWN LID: Screw down lid with breather and strainer basket.

DISCLAIMER

The material and information contained on this website is for general information purposes only. You should not rely upon the material or information on the website as a basis for making business, legal, or any other decisions. Whilst we endeavour to keep the information up to date and correct, Agpower makes no representations or warranties of any kind, express or implied about the completeness, accuracy, reliability, suitability, or availability with respect to the website or the information, products, services, or related graphics contained on the website for any purpose. Any reliance you place on such material is therefore strictly at your own risk.

CONTACT DETAILS

New & Used Machinery: Brad Storey | Mobile: 0409 138 830 | Email: administration@agpower.com.au

Spare Parts & Accessories: Trevor Phelan | Mobile: 0458 036 370 | Email: administration@agpower.com.au

Agpower & Transport Pty Ltd

 465 Maroondah Highway,
Lilydale Vic 3140

 Phone: (03) 9739 5006
 Fax: (03) 9739 5187

 /agpowerLilydale
 /agpower_and_transport_lilydale