

## SILVAN OIL DRUM KIT AIR OPERATED PUMP



Hi flow air operated oil pump, ideal for medium/high viscosity oils. This air operated oil drum kit comes complete and ready to use - just connect an air inlet hose. Includes the pump, suction tube, hose and trigger.

### PRODUCT DETAILS

<b>Brand</b>	Silvan
<b>Part No.</b>	FK0100000
<b>Weight</b>	5.5kg
<b>SKU</b>	SILVAN-FK0100000

### PRODUCT DESCRIPTION

Hi flow air operated oil pump, ideal for medium/high viscosity oils, the pump can produce up to 21.5l/min,

### DISCLAIMER

The material and information contained on this website is for general information purposes only. You should not rely upon the material or information on the website as a basis for making business, legal, or any other decisions. Whilst we endeavour to keep the information up to date and correct, Agpower makes no representations or warranties of any kind, express or implied about the completeness, accuracy, reliability, suitability, or availability with respect to the website or the information, products, services, or related graphics contained on the website for any purpose. Any reliance you place on such material is therefore strictly at your own risk.

### CONTACT DETAILS



**New & Used Machinery:** Brad Storey | Mobile: 0409 138 830 | Email: [administration@agpower.com.au](mailto:administration@agpower.com.au)

**Spare Parts & Accessories:** Trevor Phelan | Mobile: 0458 036 370 | Email: [administration@agpower.com.au](mailto:administration@agpower.com.au)

### Agpower & Transport Pty Ltd

 465 Maroondah Highway,  
Lilydale Vic 3140

 Phone: (03) 9739 5006  
 Fax: (03) 9739 5187

 /agpowerLilydale  
 /agpower\_and\_transport\_lilydale



(03) 9739 5006  465 MAROONDAH HWY, LILYDALE VIC 3140

The hose is made of synthetic rubber that is oil and water resistant with steel wire reinforcement, specifically designed for oil dispensing applications to ensure a long life,

Easy to use, lightweight trigger with flexible spout to bend and an anti-drip valve to eliminate unnecessary spills

Pump flow rate: Maximum 21.5 L/min

Operating air pressure: 3 to 8 bar

Pump materials: Air motor: technopolymer; Body: die cast steel; Seal: NBR

Suitable viscosities: Mid to high

Noise level: Below 77DB

Delivery hose: 5m Industrial grade ½" hose

Trigger mechanism: Light weight aluminium, 1.2kg Flexible spout and anti drip valve

## DISCLAIMER


The material and information contained on this website is for general information purposes only. You should not rely upon the material or information on the website as a basis for making business, legal, or any other decisions. Whilst we endeavour to keep the information up to date and correct, Agpower makes no representations or warranties of any kind, express or implied about the completeness, accuracy, reliability, suitability, or availability with respect to the website or the information, products, services, or related graphics contained on the website for any purpose. Any reliance you place on such material is therefore strictly at your own risk.



## CONTACT DETAILS



**New & Used Machinery:** Brad Storey | Mobile: 0409 138 830 | Email: [administration@agpower.com.au](mailto:administration@agpower.com.au)

**Spare Parts & Accessories:** Trevor Phelan | Mobile: 0458 036 370 | Email: [administration@agpower.com.au](mailto:administration@agpower.com.au)

## Agpower & Transport Pty Ltd

 465 Maroondah Highway,  
Lilydale Vic 3140

 Phone: (03) 9739 5006  
 Fax: (03) 9739 5187

 /agpowerLilydale  
 /agpower\_and\_transport\_lilydale