

# SILVAN P55DS 600L LINKAGE TURBOMISER SPRAYER



Linkage turbomiser 600 litre sprayer with a 140L/min centrifugal pump and a 550mm fan. Ideal for vineyards, orchards and greenhouses. Note: spray head not included

## PRODUCT DETAILS

<b>Make</b>	Silvan
<b>Model</b>	GTM-P55DS
<b>Tank Capacity</b>	600L
<b>Connection Type</b>	Linkage
<b>Pump</b>	140L/min
<b>Dimensions</b>	1150 x 1450 x 1100mm
<b>Weight</b>	250kg
<b>SKU</b>	SILVAN-GTM-P55DS

## DISCLAIMER

The material and information contained on this website is for general information purposes only. You should not rely upon the material or information on the website as a basis for making business, legal, or any other decisions. Whilst we endeavour to keep the information up to date and correct, Agpower makes no representations or warranties of any kind, express or implied about the completeness, accuracy, reliability, suitability, or availability with respect to the website or the information, products, services, or related graphics contained on the website for any purpose. Any reliance you place on such material is therefore strictly at your own risk.

## CONTACT DETAILS

**New & Used Machinery:** Brad Storey | Mobile: 0409 138 830 | Email: [administration@agpower.com.au](mailto:administration@agpower.com.au)

**Spare Parts & Accessories:** Trevor Phelan | Mobile: 0458 036 370 | Email: [administration@agpower.com.au](mailto:administration@agpower.com.au)

## Agpower & Transport Pty Ltd

 465 Maroondah Highway,  
Lilydale Vic 3140

 Phone: (03) 9739 5006  
 Fax: (03) 9739 5187

 /agpowerLilydale  
 /agpower\_and\_transport\_lilydale



(03) 9739 5006  465 MAROONDAH HWY, LILYDALE VIC 3140

## PRODUCT DESCRIPTION

Pump: CD32 centrifugal pump, 140L/min. constructed from toughened nylon. Stainless steel shaft & viton/ceramic seal.

Fan Size: P55DS:550mm dia. turbine fan, 3700 rpm. Power consumed 50 kw/70HP.

Nozzles: Air shear.

Control: Two sided electric on/off control with control box mounted in cabin. Rotary plate distribution regulators with 15 settings and manual pressure adjustment.

Frame: Galvanised RHS steel construction, cat II linkage.

## DISCLAIMER

The material and information contained on this website is for general information purposes only. You should not rely upon the material or information on the website as a basis for making business, legal, or any other decisions. Whilst we endeavour to keep the information up to date and correct, Agpower makes no representations or warranties of any kind, express or implied about the completeness, accuracy, reliability, suitability, or availability with respect to the website or the information, products, services, or related graphics contained on the website for any purpose. Any reliance you place on such material is therefore strictly at your own risk.



## CONTACT DETAILS



**New & Used Machinery:** Brad Storey | Mobile: 0409 138 830 | Email: [administration@agpower.com.au](mailto:administration@agpower.com.au)

**Spare Parts & Accessories:** Trevor Phelan | Mobile: 0458 036 370 | Email: [administration@agpower.com.au](mailto:administration@agpower.com.au)

## Agpower & Transport Pty Ltd

 465 Maroondah Highway,  
Lilydale Vic 3140

 Phone: (03) 9739 5006  
 Fax: (03) 9739 5187

 /agpowerLilydale  
 /agpower\_and\_transport\_lilydale