

# SILVAN SUPAFLO 3000L ORCHARD SPRAYER WITH POWERHEAD FAN



Trailed air assist 3000 litre Orchard sprayer with 182L/min diaphragm pump, electric controls, a Glideflex axle upgrade, wide angle shaft and Powerhead conveyor with 920mm fan. Ideal for orchards with trees up to 5 metres high.

## PRODUCT DETAILS

<b>Make</b>	Silvan
<b>Model</b>	AB64PF7G
<b>Connection Type</b>	Trailed
<b>Weight</b>	1000kg
<b>Dimensions</b>	1800 x 1755 x 3995mm
<b>Pump</b>	182 L/min
<b>Min. PTO Output</b>	75hp
<b>Tank Capacity</b>	3000L
<b>SKU</b>	SILVAN-AB64PF7G

## DISCLAIMER


The material and information contained on this website is for general information purposes only. You should not rely upon the material or information on the website as a basis for making business, legal, or any other decisions. Whilst we endeavour to keep the information up to date and correct, Agpower makes no representations or warranties of any kind, express or implied about the completeness, accuracy, reliability, suitability, or availability with respect to the website or the information, products, services, or related graphics contained on the website for any purpose. Any reliance you place on such material is therefore strictly at your own risk.



## CONTACT DETAILS

**New & Used Machinery:** Brad Storey | Mobile: 0409 138 830 | Email: [administration@agpower.com.au](mailto:administration@agpower.com.au)

**Spare Parts & Accessories:** Trevor Phelan | Mobile: 0458 036 370 | Email: [administration@agpower.com.au](mailto:administration@agpower.com.au)

## Agpower & Transport Pty Ltd

 465 Maroondah Highway,  
Lilydale Vic 3140

 Phone: (03) 9739 5006  
 Fax: (03) 9739 5187

 /agpowerLilydale  
 /agpower\_and\_transport\_lilydale



(03) 9739 5006  465 MAROONDAH HWY, LILYDALE VIC 3140

## PRODUCT DESCRIPTION

Pump: Silvan oil-backed diaphragm type with nitrile diaphragms and corrosion resistant, cast aluminium body with brass heads and manifolds. IDS2001: 182L/min. capacity 5000kPa pressure.

Fan size: 920mm axial flow type, 10 bladed fan with curved nylon reinforced blades, centrifugal clutch for soft engagement/disengagement and protective mesh cover.

Control: 40 Bar electric section valves with master valve, electric pressure regulator and in cab controls.

Nozzles: 24 flip-over nozzle bodies for dilute/concentrate spraying with on/off. 12 ceramic hollow cone nozzles per side and 12 ceramic jets with stainless steel swirl-plates per side. (16 per side with Radak conveyor).

## DISCLAIMER


The material and information contained on this website is for general information purposes only. You should not rely upon the material or information on the website as a basis for making business, legal, or any other decisions. Whilst we endeavour to keep the information up to date and correct, Agpower makes no representations or warranties of any kind, express or implied about the completeness, accuracy, reliability, suitability, or availability with respect to the website or the information, products, services, or related graphics contained on the website for any purpose. Any reliance you place on such material is therefore strictly at your own risk.

## CONTACT DETAILS

**New & Used Machinery:** Brad Storey | Mobile: 0409 138 830 | Email: [administration@agpower.com.au](mailto:administration@agpower.com.au)

**Spare Parts & Accessories:** Trevor Phelan | Mobile: 0458 036 370 | Email: [administration@agpower.com.au](mailto:administration@agpower.com.au)

### Agpower & Transport Pty Ltd

 465 Maroondah Highway,  
Lilydale Vic 3140

 Phone: (03) 9739 5006  
 Fax: (03) 9739 5187

 /agpowerLilydale  
 /agpower\_and\_transport\_lilydale