

SILVAN SUPAFLO G2 4000L SPRAYER WITH POWERHEAD FAN



Next generation trailed air assist 4000 litre G2 sprayer with 161L/min diaphragm pump, electric controls, a Glideflex axle upgrade, wide angle shaft, flush tank, chemical induction hopper and Powerhead conveyor with 920mm fan. Ideal for orchards with trees up to 5 metres high.

PRODUCT DETAILS

Make	Silvan
Model	AB43PE2G
Connection Type	Trailed
Weight	1400kg
Dimensions	2020 x 1880 x 5550mm
Pump	161 L/min
Min. PTO Output	80hp
Tank Capacity	4000L
SKU	SILVAN-AB43PE2G

DISCLAIMER

The material and information contained on this website is for general information purposes only. You should not rely upon the material or information on the website as a basis for making business, legal, or any other decisions. Whilst we endeavour to keep the information up to date and correct, Agpower makes no representations or warranties of any kind, express or implied about the completeness, accuracy, reliability, suitability, or availability with respect to the website or the information, products, services, or related graphics contained on the website for any purpose. Any reliance you place on such material is therefore strictly at your own risk.

CONTACT DETAILS

New & Used Machinery: Brad Storey | Mobile: 0409 138 830 | Email: administration@agpower.com.au

Spare Parts & Accessories: Trevor Phelan | Mobile: 0458 036 370 | Email: administration@agpower.com.au

Agpower & Transport Pty Ltd

 465 Maroondah Highway,
Lilydale Vic 3140

 Phone: (03) 9739 5006
 Fax: (03) 9739 5187

 /agpowerLilydale
 /agpower_and_transport_lilydale



(03) 9739 5006  465 MAROONDAH HWY, LILYDALE VIC 3140

PRODUCT DESCRIPTION

Pump: Silvan oil-backed diaphragm type with nitrile diaphragms and corrosion resistant, cast aluminium body with brass heads and manifolds. IDS1701:161L/min. capacity, 5000kPa pressure.

Fan size: 920mm axial flow type, 10 bladed fan with curved nylon reinforced blades, centrifugal clutch for soft engagement/disengagement and protective mesh cover.

Control: 40 Bar electric section valves with master valve, electric pressure regulator and in cab controls.

Nozzles: 24 flip-over nozzle bodies for dilute/concentrate spraying with on/off. 12 Ceramic hollow cone nozzles per side and 12 ceramic jets with stainless steel swirl plates per side. (16 per side with the Radak conveyor).

Control: 40 Bar electric section valves with master valve, electric pressure regulator and in cab controls.

DISCLAIMER


The material and information contained on this website is for general information purposes only. You should not rely upon the material or information on the website as a basis for making business, legal, or any other decisions. Whilst we endeavour to keep the information up to date and correct, Agpower makes no representations or warranties of any kind, express or implied about the completeness, accuracy, reliability, suitability, or availability with respect to the website or the information, products, services, or related graphics contained on the website for any purpose. Any reliance you place on such material is therefore strictly at your own risk.



CONTACT DETAILS



New & Used Machinery: Brad Storey | Mobile: 0409 138 830 | Email: administration@agpower.com.au

Spare Parts & Accessories: Trevor Phelan | Mobile: 0458 036 370 | Email: administration@agpower.com.au

Agpower & Transport Pty Ltd

 465 Maroondah Highway,
Lilydale Vic 3140

 Phone: (03) 9739 5006
 Fax: (03) 9739 5187

 /agpowerLilydale
 /agpower_and_transport_lilydale