

## SILVAN TRAILED STILETTO 2000L SPRAYER



Trailed air assist Stiletto 2000 litre sprayer with 161L/min diaphragm pump, electric controls, a Glideflex axle upgrade, wide angle shaft and a 900mm fan. Ideal for narrow vineyards and orchards. Additional model available with Bravo 180S automatic rate controller (DST23AB8G).

### PRODUCT DETAILS

<b>Make</b>	Silvan
<b>Model</b>	DST23AF8G
<b>Connection Type</b>	Trailed
<b>Weight</b>	640kg
<b>Dimensions</b>	1500 x 1540 x 3800mm
<b>Pump</b>	161 L/min
<b>Min. PTO Output</b>	60hp
<b>Tank Capacity</b>	2000L
<b>SKU</b>	SILVAN-DST23AF8G

### DISCLAIMER

The material and information contained on this website is for general information purposes only. You should not rely upon the material or information on the website as a basis for making business, legal, or any other decisions. Whilst we endeavour to keep the information up to date and correct, Agpower makes no representations or warranties of any kind, express or implied about the completeness, accuracy, reliability, suitability, or availability with respect to the website or the information, products, services, or related graphics contained on the website for any purpose. Any reliance you place on such material is therefore strictly at your own risk.

### CONTACT DETAILS

**New & Used Machinery:** Brad Storey | Mobile: 0409 138 830 | Email: [administration@agpower.com.au](mailto:administration@agpower.com.au)

**Spare Parts & Accessories:** Trevor Phelan | Mobile: 0458 036 370 | Email: [administration@agpower.com.au](mailto:administration@agpower.com.au)

### Agpower & Transport Pty Ltd

 465 Maroondah Highway,  
Lilydale Vic 3140

 Phone: (03) 9739 5006  
 Fax: (03) 9739 5187

 /agpowerLilydale  
 /agpower\_and\_transport\_lilydale



(03) 9739 5006  465 MAROONDAH HWY, LILYDALE VIC 3140

## PRODUCT DESCRIPTION

Pump: Silvan oil-backed diaphragm type with nitrile diaphragms and corrosion resistant, cast anodised aluminium body with brass heads and manifolds. IDS1701: 161L/min. capacity 5000kPa pressure.

Fan size: 900mm axial flow type, 10 bladed fan with curved nylon reinforced blades, air straightening vanes and protective mesh cover.

Nozzles: Flip-over type for dilute/concentrate spraying. Ceramic jets, stainless steel swirl-plates, 16 nozzles with twist on/off.

Control: 40 bar electric section valves, master valve, electric pressure regulator and in cab controls.

## DISCLAIMER


The material and information contained on this website is for general information purposes only. You should not rely upon the material or information on the website as a basis for making business, legal, or any other decisions. Whilst we endeavour to keep the information up to date and correct, Agpower makes no representations or warranties of any kind, express or implied about the completeness, accuracy, reliability, suitability, or availability with respect to the website or the information, products, services, or related graphics contained on the website for any purpose. Any reliance you place on such material is therefore strictly at your own risk.



## CONTACT DETAILS



**New & Used Machinery:** Brad Storey | Mobile: 0409 138 830 | Email: [administration@agpower.com.au](mailto:administration@agpower.com.au)

**Spare Parts & Accessories:** Trevor Phelan | Mobile: 0458 036 370 | Email: [administration@agpower.com.au](mailto:administration@agpower.com.au)

## Agpower & Transport Pty Ltd

 465 Maroondah Highway,  
Lilydale Vic 3140

 Phone: (03) 9739 5006  
 Fax: (03) 9739 5187

 /agpowerLilydale  
 /agpower\_and\_transport\_lilydale