

SILVAN TRAILED SUPAFLO 3500L SPRAYER



Trailed air assist Supaflo 3500 litre sprayer with 161L/min diaphragm pump, electric controls, a Glideflex axle upgrade, wide angle shaft and a 900mm fan. Ideal for orchards with trees up to 4 metres high. Additional model available with 249L/min pump (DAB36AF7G).

PRODUCT DETAILS

Make	Silvan
Model	DAB33AF7G
Connection Type	Trailed
Weight	800kg
Dimensions	1800 x 1830 x 4755mm
Pump	161 L/min
Min. PTO Output	80hp
Tank Capacity	3500L
SKU	SILVAN-DAB33AF7G

DISCLAIMER

The material and information contained on this website is for general information purposes only. You should not rely upon the material or information on the website as a basis for making business, legal, or any other decisions. Whilst we endeavour to keep the information up to date and correct, Agpower makes no representations or warranties of any kind, express or implied about the completeness, accuracy, reliability, suitability, or availability with respect to the website or the information, products, services, or related graphics contained on the website for any purpose. Any reliance you place on such material is therefore strictly at your own risk.

CONTACT DETAILS

New & Used Machinery: Brad Storey | Mobile: 0409 138 830 | Email: administration@agpower.com.au

Spare Parts & Accessories: Trevor Phelan | Mobile: 0458 036 370 | Email: administration@agpower.com.au

Agpower & Transport Pty Ltd

 465 Maroondah Highway,
Lilydale Vic 3140

 Phone: (03) 9739 5006
 Fax: (03) 9739 5187

 /agpowerLilydale
 /agpower_and_transport_lilydale



(03) 9739 5006  465 MAROONDAH HWY, LILYDALE VIC 3140

PRODUCT DESCRIPTION

Pump: Silvan oil-backed diaphragm type with nitrile diaphragms and corrosion resistant, anodised cast aluminium body with brass heads and manifolds. IDS1701: 161L/min. capacity, 5000kPa pressure.

Fan size: 900mm axial flow type, 10 bladed fan with curved nylon reinforced blades with air straightening vanes and protective mesh cover. Powerhead and Radak fitted with 920mm axial flow type, 10 bladed fan, centrifugal clutch and protective mesh cover.

Control: 40 Bar electric section valves with master valve, electric pressure regulator and in cab controls.

Nozzles: Flip-over type for dilute/concentrate spraying. Ceramic jets, stainless steel swirl-plates. 16 double sided nozzles (8 per side) twist on/off. The Powerhead has 24 double sided nozzles (12 per side) and the Radak has 32 (16 per side).

DISCLAIMER

The material and information contained on this website is for general information purposes only. You should not rely upon the material or information on the website as a basis for making business, legal, or any other decisions. Whilst we endeavour to keep the information up to date and correct, Agpower makes no representations or warranties of any kind, express or implied about the completeness, accuracy, reliability, suitability, or availability with respect to the website or the information, products, services, or related graphics contained on the website for any purpose. Any reliance you place on such material is therefore strictly at your own risk.



CONTACT DETAILS

New & Used Machinery: Brad Storey | Mobile: 0409 138 830 | Email: administration@agpower.com.au

Spare Parts & Accessories: Trevor Phelan | Mobile: 0458 036 370 | Email: administration@agpower.com.au

Agpower & Transport Pty Ltd

 465 Maroondah Highway,
Lilydale Vic 3140

 Phone: (03) 9739 5006
 Fax: (03) 9739 5187

 /agpowerLilydale
 /agpower_and_transport_lilydale