

TORO TITAN MR4800 MYRIDE 48" (122CM) (75316TA)



You've got bigger fish to fry than mowing your lawn - literally! Don't let your territory's bumpy terrain tame your plans. Featuring the same technology used in our commercial line, the Toro 48" TITAN is the perfect fit of pro power and luxury comfort to dominate your lawn. Save your body from the toughest terrain and avoid slow mowing speeds with the MyRIDE Suspension System.

PRODUCT DETAILS

Make	Toro
Model	75316TA
Horsepower	24 hp*
CC's	726cc
Engine	Kawasaki FR730V
Deck Size	122cm (48") IronForged Fabricated 10 ga. High Strength with Bull Nose
SKU	TORO75316TA

DISCLAIMER

The material and information contained on this website is for general information purposes only. You should not rely upon the material or information on the website as a basis for making business, legal, or any other decisions. Whilst we endeavour to keep the information up to date and correct, Agpower makes no representations or warranties of any kind, express or implied about the completeness, accuracy, reliability, suitability, or availability with respect to the website or the information, products, services, or related graphics contained on the website for any purpose. Any reliance you place on such material is therefore strictly at your own risk.

CONTACT DETAILS

New & Used Machinery: Brad Storey | Mobile: 0409 138 830 | Email: administration@agpower.com.au

Spare Parts & Accessories: Trevor Phelan | Mobile: 0458 036 370 | Email: administration@agpower.com.au

Agpower & Transport Pty Ltd

 465 Maroondah Highway,
Lilydale Vic 3140

 Phone: (03) 9739 5006
 Fax: (03) 9739 5187

 /agpowerLilydale
 /agpower_and_transport_lilydale



(03) 9739 5006 📞 465 MAROONDAH HWY, LILYDALE VIC 3140

PRODUCT DESCRIPTION

You've got bigger fish to fry than mowing your lawn - literally. Don't let your territory's bumpy terrain tame your plans. Featuring the same technology used in our commercial line, the Toro 122 cm TITAN is the perfect fit of pro power and luxury comfort to dominate your lawn. Save your body from the toughest terrain and avoid slow mowing speeds with the MyRIDE Suspension system. And you'll have pro-level confidence with a commercial drop pin height of cut and a rubber discharge chute. And this beast is meant to last, with a wide front tubular axle, huge front tyres and a reinforced 10-Gauge high strength deck edge with triangle bullnose.

Key Features:

- Kawasaki FR730V
- Cast Aluminum Stomp Pad
- Handcrafted Seat with Arm Rests
- Comfortable: MyRIDE Suspension System features a fully suspended operator platform.
- Tough: Toro 48" IronForged fabricated deck and cast aluminium stomp pad.
- Versatile: Easy height adjustment, rubber discharge chute and wet spray blocking fenders.
- Convenient: Handcrafted high-back seat with arm rests and built-in cup holder.

*As configured to meet safety, emission and operating requirements, the actual engine horsepower on this mower may be significantly lower.

†See retailer for complete warranty details.

DISCLAIMER

The material and information contained on this website is for general information purposes only. You should not rely upon the material or information on the website as a basis for making business, legal, or any other decisions. Whilst we endeavour to keep the information up to date and correct, Agpower makes no representations or warranties of any kind, express or implied about the completeness, accuracy, reliability, suitability, or availability with respect to the website or the information, products, services, or related graphics contained on the website for any purpose. Any reliance you place on such material is therefore strictly at your own risk.

CONTACT DETAILS

New & Used Machinery: Brad Storey | Mobile: 0409 138 830 | Email: administration@agpower.com.au

Spare Parts & Accessories: Trevor Phelan | Mobile: 0458 036 370 | Email: administration@agpower.com.au

Agpower & Transport Pty Ltd

📍 465 Maroondah Highway,
Lilydale Vic 3140

📞 Phone: (03) 9739 5006
📠 Fax: (03) 9739 5187

📘 /agpowerLilydale
📷 /agpower_and_transport_lilydale