

VICON EXTRA 7100T VARIO MOWER CONDITIONER



The all-new EXTRA 7100T Vario delivers an outstanding performance with its completely new suspension concept, 10.20m working width and hydraulic adjustment of working width and overlap. EXTRA 7100T is fitted with the new Vicon suspension concept called QuattroLink. The mowing unit is pulled by four suspension arms fitted onto a fixed carrying arm that allows the mowing unit to float independently over the field, adjusting highly accurately and instantly to any changes in ground contours.

PRODUCT DETAILS

Make	Vicon
Model	Extra 7100T Vario
Working Width	9800 - 10200mm
No. Discs	2×10
Conditioner	SemiSwing Steel Tines
SKU	VICON-EXTRA7100T

PRODUCT DESCRIPTION

- Up to 10.20m working width.
- New innovative QuattroLink racecar suspension concept.
- Flexible suspension - 700mm movements, 400mm upwards and 300mm downwards.

DISCLAIMER

The material and information contained on this website is for general information purposes only. You should not rely upon the material or information on the website as a basis for making business, legal, or any other decisions. Whilst we endeavour to keep the information up to date and correct, Agpower makes no representations or warranties of any kind, express or implied about the completeness, accuracy, reliability, suitability, or availability with respect to the website or the information, products, services, or related graphics contained on the website for any purpose. Any reliance you place on such material is therefore strictly at your own risk.

CONTACT DETAILS

New & Used Machinery: Brad Storey | Mobile: 0409 138 830 | Email: administration@agpower.com.au

Spare Parts & Accessories: Trevor Phelan | Mobile: 0458 036 370 | Email: administration@agpower.com.au

Agpower & Transport Pty Ltd

📍 465 Maroondah Highway,
Lilydale Vic 3140

📞 Phone: (03) 9739 5006
📠 Fax: (03) 9739 5187

📘 /agpowerLilydale
📷 /agpower_and_transport_lilydale



(03) 9739 5006 📞 465 MAROONDAH HWY, LILYDALE VIC 3140

- NonStop BreakAway protection across full working width.
- Hydraulic adjustment of overlap on the go.
- Ground pressure remains the same, even when overlap is changed.
- Minimum 500mm ground clearance during headland turns.
- Dual adjustment of conditioner hood - both front and rear end can be adjusted.
- Integrated parking feet for vertical storage.
- Counter-rotating triangular discs.

DISCLAIMER

The material and information contained on this website is for general information purposes only. You should not rely upon the material or information on the website as a basis for making business, legal, or any other decisions. Whilst we endeavour to keep the information up to date and correct, Agpower makes no representations or warranties of any kind, express or implied about the completeness, accuracy, reliability, suitability, or availability with respect to the website or the information, products, services, or related graphics contained on the website for any purpose. Any reliance you place on such material is therefore strictly at your own risk.

CONTACT DETAILS

New & Used Machinery: Brad Storey | Mobile: 0409 138 830 | Email: administration@agpower.com.au

Spare Parts & Accessories: Trevor Phelan | Mobile: 0458 036 370 | Email: administration@agpower.com.au

Agpower & Transport Pty Ltd

📍 465 Maroondah Highway,
Lilydale Vic 3140

📞 Phone: (03) 9739 5006
📠 Fax: (03) 9739 5187

📘 /agpowerLilydale
📷 /agpower_and_transport_lilydale