

VICON EXTRA 732R REAR MOUNTED MOWER CONDITIONER



EXTRA 732T-732R-736T are powerful mower conditioners with superb ground tracking, thanks to the new innovative QuattroLink suspension concept. With its' accurate tracking ability and highly flexible working range this suspension provides unrivalled cutting performance. Like a race car you want better tracking, ability to go at faster speed and adjust instantly to changing field conditions when operating your mower conditioner. These are the main benefits you will experience when running the EXTRA 700 series.

PRODUCT DETAILS

Make	Vicon
Model	Extra 732R
Working Width	3180mm
No. Discs	8 Triangular Discs
Conditioner	Roller Conditioner
Min. Power Required	74/100 kW/hp
SKU	VICON-EXTRA732R

DISCLAIMER

The material and information contained on this website is for general information purposes only. You should not rely upon the material or information on the website as a basis for making business, legal, or any other decisions. Whilst we endeavour to keep the information up to date and correct, Agpower makes no representations or warranties of any kind, express or implied about the completeness, accuracy, reliability, suitability, or availability with respect to the website or the information, products, services, or related graphics contained on the website for any purpose. Any reliance you place on such material is therefore strictly at your own risk.

CONTACT DETAILS

New & Used Machinery: Brad Storey | Mobile: 0409 138 830 | Email: administration@agpower.com.au

Spare Parts & Accessories: Trevor Phelan | Mobile: 0458 036 370 | Email: administration@agpower.com.au

Agpower & Transport Pty Ltd

 465 Maroondah Highway,
Lilydale Vic 3140

 Phone: (03) 9739 5006
 Fax: (03) 9739 5187

 /agpowerLilydale
 /agpower_and_transport_lilydale



(03) 9739 5006  465 MAROONDAH HWY, LILYDALE VIC 3140

PRODUCT DESCRIPTION

- 3.18 and 3.50m working width.
- New innovative QuattroLink racecar suspension concept.
- Flexible suspension – 700mm movements, 400mm upwards and 300mm downwards.
- Hydraulic setting of ground pressure.
- NonStop BreakAway protection across full working width.
- 150mm mechanical adjustment of overlap.
- Minimum 500mm ground clearance during headland turns.
- Dual adjustment of conditioner hood - both front and rear end can be adjusted.
- Integrated parking feet for vertical storage.
- Vertical Transport Solution.
- Counter-rotating triangular discs

DISCLAIMER

The material and information contained on this website is for general information purposes only. You should not rely upon the material or information on the website as a basis for making business, legal, or any other decisions. Whilst we endeavour to keep the information up to date and correct, Agpower makes no representations or warranties of any kind, express or implied about the completeness, accuracy, reliability, suitability, or availability with respect to the website or the information, products, services, or related graphics contained on the website for any purpose. Any reliance you place on such material is therefore strictly at your own risk.

CONTACT DETAILS

New & Used Machinery: Brad Storey | Mobile: 0409 138 830 | Email: administration@agpower.com.au

Spare Parts & Accessories: Trevor Phelan | Mobile: 0458 036 370 | Email: administration@agpower.com.au

Agpower & Transport Pty Ltd

 465 Maroondah Highway,
Lilydale Vic 3140

 Phone: (03) 9739 5006
 Fax: (03) 9739 5187

 /agpowerLilydale
 /agpower_and_transport_lilydale