








- 











Trinciatrice da vigneto e frutteto per erba e sarmenti fino a \varnothing 4-5 cm., da applicare a trattori con potenza compresa tra 30 e 60 HP.
- 

Broyeur à vignobles et vergers indiqué pour broyer l'herbe, les buissons et les sarments allant jusqu'à \varnothing 4-5 cm., pour les tracteurs de 30 à 60 CV.
- 

Mulcher for vineyard and orchard, suited to mulch grass, bushes and pruning up to \varnothing 4-5 cm. For tractors from 30 to 60 HP.
- 

Trituradora para viñedos y frutales. Apta para triturar hierba y material leñoso de hasta 4-5 cm. de diámetro para tractores con una potencia entre 30 y 60 CV.
- 

Gerät für den Wein- und Obstbau, für Traktoren von 30 bis 60 PS. Es eignet sich zum Mulchen von Gras, Büsche und Reisig bis \varnothing 4-5 cm.

Mod.													
	cm	Min	Max	mm	n°	n°	n°	PTO	A	B	C	Kg	
AF 105	105	30	60	615 435 245 805	10	30	3	540 (1000)	85	120	100	340	
AF 115	115	30	60	615 535 245 905	10	30	3	540 (1000)	85	130	100	360	
AF 125	125	30	60	715 535 345 905	12	36	3	540 (1000)	85	140	100	380	
AF 135	135	30	60	715 635 345 1005	12	36	3	540 (1000)	85	150	100	395	
AF 145	145	30	60	715 735 345 1105	14	42	3	540 (1000)	85	160	100	410	
AF 160	160	30	60	715 885 345 1255	14	42	3	540 (1000)	85	175	100	435	
AF 180	180	30	60	715 1085 345 1455	16	48	3	540 (1000)	85	195	100	470	

Il peso è riferito alla macchina standard (senza accessori) • The weight refers to the machine with standard equipment (without accessories) • Die Gewichtsangabe bezieht sich auf die Maschine in Grundausstattung (ohne Sonderausstattung) • Le poids se réfère à la machine standard (sans accessoires) • El peso se refiere al estándar de la máquina (sin accesorios).




- Attacco spostabile meccanicamente, Cat. I.
- Displaceable three point linkage, Cat. I (mechanical).
- Versetzbarer Dreipunktbock, Kat. I (mechanischer).
- Attelage déportable à 3 points, Cat. I (mécanique).
- Enganche a los 3 puntos del tractor desplazable, Cat. I (desplazamiento mecánico).



- Rullo livellatore regolabile con pulirullo.
- Adjustable and levelling roller, with scraper.
- Einstellbare Stützwalze mit Abstreifer.
- Rouleau palpeur réglable avec décattoir.
- Rodillo nivelador con rascador.



- Fiancata destra arrotondata e priva di sporgenze.
- Chamfered profile on the right hand side, with no juts.
- Seitlich Abschrägung auf Rahmen, ohne Vorsprungen.
- Coin côté droit arrondi et sans saillies.
- Perfil derecho rematado sin bordes salientes.



Optional

OPTIONALS



- Spostamento idraulico con tubi e innesti rapidi.
- Hydraulic side shift with hoses and quick couplings.
- Hydraulische Seitenverschiebung.
- Déport hydraulique avec tuyaux et prises rapides.
- Desplazamiento hidráulico.



- Slitte di appoggio.
- Skids.
- Satz Kufen.
- Jeu patins.
- Patines.




- Attacco centrale.
- Centre mounted linkage.
- Mittiger Anbau.
- Attelage axial.
- Enganche central.



- Kit ruote sterzanti.
- Steering wheels.
- Satz Hinterlenkräder.
- Jeu roues directrices.
- Ruedas directrices.



- Albero cardanico.
- Pto drive shaft.
- Gelenkwelle.
- Arbre cardan.
- Cardan.

Mod.		
	mm	
AF 125	858 392	485 765
	923 427	
AF 135	550 800	923 527
	550 900	
AF 145	893 707	
	520 1080	
AF 160	893 907	
	520 1280	