



CS-501SX

**LIGHT WEIGHT SAW WITH
INCREASED POWER**



DEPEND ON IT

FEATURES & BENEFITS



DROPOUT PREVENTION NUTS



SIDE ACCESS CHAIN TENSIONER

ROTATING PLASTIC CHAIN CATCHER



ALUMINUM HANDLE WITH RUBBER GRIP

DECOMPRESSION VALVE

TOOL-LESS AIR FILTER COVER

G-FORCE AIR PRE-CLEANER SYSTEM



STARTER ASSIST GRIP CAPS

TRANSLUCENT FUEL TANK

Engine Displacement (cm ³)	Dry Weight* (kg)	Output (kW/ps)	Fuel Tank Capacity (L)	Oil Tank Capacity (L)	Guide Bar Length (cm)	Saw Chain Pitch (inch)	Gauge (inch)
50.2	4.7	2.75 /3.50	0.50	0.28	40,45,50	0.325	0.058

*without guide bar & saw

- // Dual-post chain brake for extra durability
- // Inertia-type chain brake for safety.
- // Tool-less air filter cover for easy access.
- // Vibration-reduction system for operator comfort.
- // G-Force Engine Air Pre-Cleaner for reduced air filter maintenance.
- // Side access chain tensioner for quick chain adjustment.
- // Aluminum handle with rubber grip for improved comfort.
- // Replaceable, metal bumper spike for improved control.

- // Rotating plastic chain catcher.
- // Rubber double molding rear handle for operator comfort.
- // Inboard clutch for easy maintenance and easy bar and chain replacement.
- // Magnesium die-cast crankcase for lightweight and durability.
- // Oil / fuel caps opening by recoil starter grip.
- // Decompression valve for easy starting.
- // Translucent fuel tank for easy level checks.
- // Dropout prevention guide bar nuts.



Specifications, descriptions, and illustrative materials in this literature are as accurate as known at the time of publication, but are subject to change without notice.

YNPN-15-0503E



DEPEND ON IT