



## **TRAIL**

- 75 100 HP
- High Performance On Demand True All-Wheel-Drive (AWD)
- · Electronic Power Steering
- Independent Rear Suspension, 25.4CM 33.5CM Of Travel
- Lock & Ride®

## **MULTI-TERRAIN**

- 110 181 HP
- High Performance On Demand True All-Wheel-Drive (AWD) / Isolated Xtreme Performance On Demand True All-Wheel-Drive (AWD)
- Independent Rear Suspension, 45.7CM 50.8CM Of Travel
- Walker Evans Needle Shocks / Fox® 2.5 Podium Live Valve Shocks
- GPS Ride Command 7" Touch Screen Display

## WIDE OPEN

- 181 225 HP
- High Performance On Demand True All-Wheel-Drive (AWD) / Isolated Xtreme Performance On Demand True All-Wheel-Drive (AWD)
- 32" Tyres with 15" Painted Cast Aluminium Wheels
- Walker Evans Needle Shocks / Fox® 2.5 Podium Live Valve Shocks
- · Rockford Fosgate Audio

## **PSLARIS**

# GENUINE PARTS & ACCESSORIES

"MAKE IT YOUR OWN"



FOR YOUR COMFORT, SAFETY & PROTECTION



Mark Larkham talks about Polaris Genuine Accessories .

### **SOME OF OUR MOST POPULAR ACCESSORIES**



8. Stage 5 Audio Upgrade by Rockford Fosgate®

9. Lock & Ride Poly Rear Panel, 4-Seat

## 2023 MODEL LINE UP









INDEPENDENT

REAR SUSPENSION -

45.7CM OF TRAVEL

ON DEMAND TRUE

ALL-WHEEL-DRIVE

TRAILING ARM

BAR 50.8CM

USABLE TRAVEL

WITH STABILIZER REAR WALKER

EVANS NEEDLE

SHOCKS

110 HP



USABLE TRAVEL



## TURBO R SPORT - 74"









32" TYRES WITH 15" PAINTED CAST ALUMINIUM WHEELS

USABLE TRAVEL

TRAILING ARM WITH STABILIZER BAR 71.9CM

WALKER EVANS VELOCITY SERIES SHOCKS







181 HP

TURBOCHARGED

ISOLATED XTREME PERFORMANCE TRUE ON-DEMAND AWD/2WD



TRAILING ARM COMMAND 7" WITH STABILIZER TOUCH SCREEN BAR 71.9CM DISPLAY USABLE TRAVEL



VALVE X2 SHOCKS



#### TURBO R 4 ULTIMATE- 74"





181 HP TURBOCHARGED



GPS RIDE COMMAND 7" TOUCH SCREEN DISPLAY



FOX® 3.0 LIVE VALVE X2

TRAILING ARM WITH STABILIZER BAR 71.9CM USABLE TRAVFI



#### PRO R ULTIMATE - 74"







4-WHEEL

HYDRAULIC DISC

BORE FRONT AND

DUAL-BORE REAR



BOXED TRAILING

ARM WITH

STABILIZER BAR

73.7CM USABLE



X2 SHOCKS



F0X® 3.0 GPS RIDE LIVE VALVE

COMMAND 7" TOUCH SCREEN







FOX® 3.0 LIVE VALVE X2 SHOCKS



BOXED TRAILING ARM WITH TOUCH SCREEN STABILIZER BAR 73.7CM USABLE TRAVFI



ROCKFORD FOSGATE





REAR

TRAVFI



HIGH PERFORMANCE INDEPENDENT 2" FRONT/2.5" REAR ON DEMAND TRUE ALL-WHEEL-DRIVE SUSPENSION -50.8CM OF WHEEL







WALKER EVANS HYDRAULIC DISC NEEDLE SHOCKS WITH DUAL-BORE FRONT AND REAR CALIPERS







ISOLATED XTRFMF TURBOCHARGED PERFORMANCE ON DEMAND TRUE ALL-WHEEL-



REAR SUSPENSION - 50.8CM OF WHEEL TRAVEL TECHNOLOGY

2" FRONT/2.5" REAR FOX® SHOCKS STABILIZER WITH POSITION SENSITIVE SPIRAL

TRAILING ARM BAR 55.9CM IISARI F TRAVEL







TURBOCHARGED



INDEPENDENT

REAR SUSPENSION

ISOLATED.

XTRFMF

PERFORMANCE

ON DEMAND

TRUE ALL-



- 50.8CM OF WHEEL LIVE VALVE



F0X® 2.5

PODIUM



POWER

STEERING





## SIMON EVANS / JACKSON EVANS

#### **POLARIS RACING DRIVERS**

Simon Evans is a hard-charging champion with four Australian Rally Championships to his name. In 2018 he won the Australian SXS Championship in his RZR XP Turbo S.

In 2019 Jackson Evans in his RZR XP Turbo S over took his father and the rest of the competitive field to win the 2019 Australian SXS Championship. Like father like son.

In 2020, the race season was cancelled due to a world pandemic but the boys will be back in 2021.

f/simoneevansmotorsport

/ jackson\_evans\_utv



## **EDEN EVANS**

#### **POLARIS RACING DRIVERS**

Eden Evans, the daughter of rallying and SXS racing legend Simon Evans, made her racing debut in the opening round of the Kincrome Motorsport Australia SXS Championship.

@/edenevanss\_









RZR TRAIL S 1000 PREMIUM - 60"



RZR XP 1000 SPORT - 64"



RZR PRO XP SPORT - 64"

Engine Type	4-Stroke DOHC Twin Cylinder	4-Stroke DOHC Twin Cylinder	4-Stroke DOHC Twin Cylinder	4-Stroke DOHC Twin Cylinder Turbocharged
Displacement	875cc	999cc	999cc	925cc
Fuel System / Battery	Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection
Cooling	Liquid	Liquid	Liquid	Liquid
Transmission/ Final Drive	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H
Drive System	True On-Demand AWD/2WD	High Performance True On-Demand AWD/2WD	High Performance True On-Demand AWD/2WD	Isolated Xtreme Performance True On-Demand AWD/2WD
Engine Braking System / Active Descent Control	Yes / Not Equipped	Not Equipped / Not Equipped	Not Equipped / Not Equipped	Not Equipped / Not Equipped
Front Suspension	Dual A-Arm with Stabilizer Bar and 25.4 cm Wheel Travel	Dual A-Arm with Stabilizer Bar and 31.1 cm Wheel Travel	Dual A-Arm with Stabilizer Bar and 50.8 cm Usable Travel*, 40.6 cm of Wheel Travel	High-Clearance Dual A-Arm with Stabilizer Bar and 50.8 cm Usable Travel*, 43.2 cm Wheel Travel
Rear Suspension	Dual A-Arm with Stabilizer Bar and 25.4 cm Wheel Travel	Dual A-Arm with Stabilizer Bar and 33.5 cm Wheel Travel	Trailing Arm with Stabilizer Bar and 50.8 cm Usable Travel*, 45.7 cm of Wheel Travel	Trailing Arm & Standard-Clearance Radius Rods with Stabilizer Bar and 55.9 cm Usable Travel*, 50.8 cm Wheel Travel
Front/Rear Brakes	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers	4-Wheel Hydraulic Disc with Triple-Bore Front and Dual-Bore Rear Calipers
Parking Brake	Park in Transmission	Park in Transmission	Park in Transmission	Park in Transmission
Front Tyres	26 X 8 X 12; PXT	27 x 9-12; Trailmaster A/T	29 x 9-14; Radial Tire	30 x 10-14 MAXXIS Carnivore; Wheel Size 14x6
Rear Tyres	26 X 9 X 12; PXT	27 x 11-12; Trailmaster A/T	29 x 11-14; Radial Tire	30 x 10-14 MAXXIS Carnivore; Wheel Size 14x7
Wheels	Stamped Steel	Cast Aluminum	Cast Aluminum	Cast Aluminum
Wheelbase	200.7 cm	200.7 cm	228.6 cm	244 cm
Dry Weight	561.5 kg	600 kg	662 kg	796Kg
Overall Vehicle Size (L x W x H)	282 x 127 x 172.5 cm	282 x 152.4 x 176 cm	302.2 x 162.6 x 187.3 cm	320 x 162.6 x 182.1 cm
Ground Clearance	27.9 cm	31.8 cm	35.6 cm	36.8 cm
Seating Capacity	2	2	2	2
Fuel Capacity	35.9 L	35.9 L	35.9 L	45.4 L
Bed Box Dimensions (L x W x H)	52.5 x 94 x 20 cm	52.5 x 94 x 20 cm	72.0 x 57.0 x 17.8 cm	66 x 45 x 29.2 cm
Front/Rear Rack or Box Capacity	N.A. / 136 kg	N.A. / 136 kg	N.A. / 136 kg	N.A. / 136 kg
Payload Capacity	336 kg	336 kg	336 kg	336 kg
Hitch Towing Rating		680 kg	N/A	N/A
Hitch Type	Standard 3.2 cm Receiver	Standard 3.2 cm Receiver	Not Equipped	Not Equipped
Cargo System/Cab	Lock & Ride®	Lock & Ride®	Lock & Ride®	Lock & Ride®
Lighting	Halogen 55W low/ 60W high & Red LED Tail/Brake Lights	Front Blacked Out Signature White LED Low/High with Accent Lights & Red LED Tail / Brake Lights	Signature White LED, Low/High & Red LED Tail / Brake Lights	White LED Low/High & Red LED Tail / Brake Lights
Electronic Power Steering	No	Yes	Standard with Quick Turn Rack	High Assist Electronic Power Steering with Quick Turn Rack; Race Inspire Steering Wheel
Instrumentation	Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speed-ometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder Light, Gear Indicator, DC Outlet + 12V Power Plug.	Dual-sweep Analog Dials w/ 4° LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder Light, Gear Indicator, DC Outlet + 12V Power Plug	Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedom- eter, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder Light, Gear Indicator, DC Outlet	Dual-sweep Analog Dials w/ 4° LCD Rider Information Center: User Selectat Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speed eter, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, F Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat & Reminder Light, Gear Indicator, DC Outlet
Other Standard Features	Adjustable Tilt Steering, Near Field Communication Technology	Adjustable Tilt Steering, Near Field Communication Technology, Polaris P.A.S.S.	Adjustable Tilt Steering	High Output 900w charging system with sealed electrical, Polaris Pulse system In-Dash Charge Port, Polaris P.A.S.S.







RZR PRO XP ULTIMATE - 64"

RZR XP 4 1000 PREMIUM EPS - 64"

RZR PRO XP 4 SPORT - 64"

D7D	PRO	VD	4 111	TIM	ATE	C.

	Engine Type	4-Stroke DOHC Twin Cylinder Turbocharged	4-Stroke DOHC Twin Cylinder	4-Stroke DOHC Twin Cylinder Turbocharged	4-Stroke DOHC Twin Cylinder Turbocharged
ENGINE	Displacement	925cc	999cc	925cc	925cc
ENG	Fuel System / Battery	Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection
	Cooling	Liquid	Liquid	Liquid	Liquid
AIN	Transmission/ Final Drive	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H
DRIVETRAIN	Drive System	Isolated Xtreme Performance True On-Demand AWD/2WD	High Performance True On-Demand AWD/2WD	Isolated Xtreme Performance True On-Demand AWD/2WD	Isolated Xtreme Performance True On-Demand AWD/2WD
품	Engine Braking System / Active Descent Control	Not Equipped / Not Equipped	Not Equipped / Not Equipped	Not Equipped / Not Equipped	Not Equipped / Not Equipped
NOISI	Front Suspension	High-Clearance Dual A-Arm with Stabilizer Bar and 50.8 cm Usable Travel*, 43.2 cm Wheel Travel	Dual A-Arm with Stabilizer Bar and 50.8 cm Usable Travel*, 40.6 cm of Wheel Travel	High-Clearance Dual A-Arm with Stabilizer Bar and 50.8 cm Usable Travel*, 43.2 cm Wheel Travel	High-Clearance Dual A-Arm with Stabilizer Bar and 50.8 cm Usable Travel*, 43.2 cm Wheel Travel
SUSPENSION	Rear Suspension	Trailing Arm & Standard-Clearance Radius Rods with Stabilizer Bar and 55.9 cm Usable Travel*, 50.8 cm Wheel Travel	Trailing Arm with Stabilizer Bar and 50.8 cm Usable Travel*, 45.7 cm of Wheel Travel	Trailing Arm & Standard-Clearance Radius Rods with Stabilizer Bar and 55.9 cm Usable Travel*, 50.8 cm Wheel Travel	Trailing Arm & Standard-Clearance Radius Rods with Stabilizer Bar and 55.9 cm Usable Travel*, 50.8 cm Wheel Travel
BRAKES	Front/Rear Brakes	4-Wheel Hydraulic Disc with Triple-Bore Front and Dual-Bore Rear Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers	4-Wheel Hydraulic Disc with Dual-Bore XL Front and Dual-Bore Rear Calipers	4-Wheel Hydraulic Disc with Dual-Bore XL Front and Dual-Bore Rear Calipers
	Parking Brake	Park in Transmission	Park in Transmission	Park in Transmission	Park in Transmission
TYRES AND WHEELS	Front Tyres	30 x 10-14 MAXXIS Carnivore (8-Ply); Wheel Size 14x6	29 x 9-14; Radial Tire	30 x 10-14 Maxxis Carnivore II; (8-ply rated); Wheel Size 14x6	30 x 10-14 Maxxis Carnivore II; (8-ply rated); Wheel Size 14x6
ESA	Rear Tyres	$30 \times 10$ -14 MAXXIS Carnivore (8-Ply); Wheel Size 14x7	29 x 11-14; Radial Tire	30 x 10-14 Maxxis Carnivore II; (8-ply rated); Wheel Size 14x7	30 x 10-14 Maxxis Carnivore II; (8-ply rated); Wheel Size 14x7
₹ ≥	Wheels	Cast Aluminum	Cast Aluminum	Cast Aluminum	Cast Aluminum
	Wheelbase	244 cm	297.2 cm	317.5 cm	317.5 cm
	Dry Weight	814 kg	762 kg	916 kg	937 kg
S	Overall Vehicle Size (L x W x H)	320 x 163 x 182 cm	370.8 x 162.6 x 187.3 cm	393.7 x 162.6 x 186.9 cm	393.7 x 162.6 x 186.9 cm
Ë	Ground Clearance	36.8 cm	35.6 cm	36.8 cm	36.8 cm
APA	Seating Capacity	2	4	4	4
S/C	Fuel Capacity	45.4 L	35.9 L	49.2 L	49.2 L
DIMENSIONS / CAPACITIES	Bed Box Dimensions (L x W x H)	66 x 45 x 29.2 cm	72.0 × 57.0 × 17.8 cm	66 x 45 x 29.2 cm	66 x 45 x 29.2 cm
DIME	Front/Rear Rack or Box Capacity	N.A. / 136 kg	N.A. / 136 kg	N.A. / 136 kg	N.A. / 136 kg
	Payload Capacity	336 kg	408 kg	408 kg	408 kg
	Hitch Towing Rating	N/A	N/A	N/A	N/A
	Hitch Type	Not Equipped	Not Equipped	Not Equipped	Not Equipped
	Cargo System/Cab	Lock & Ride®	Lock & Ride®	Lock & Ride®	Lock & Ride® Fold Flat Rear Storage, convertible rear seat storage with integrated tie down points, 70.4 x 134.1 x 49.53 cm
	Lighting -	Signature White LED, Low / High & Red LED Tail / Brake Lights; Front & Rear LED Accent Lights	Front Blacked Out Signature White LED Low/High w/ Accent Lights & Red LED Tail / Brake Lights	Signature White LED, Low/High & Red LED Tail / Brake Lights	Signature White LED, Low / High & Red LED Tail / Brake Lights; Front & Rear LED Accent Lights; Interior Accent Lighting
	Electronic Power Steering	High Assist Electronic Power Steering with Quick Turn Rack; Race inspired Steering Wheel with Tilt and Telescoping adjustment; Dynamix and Ride Command Push Button Controls	Standard with Quick Turn Rack	High Assist Electronic Power Steering with Quick Turn Rack; Race Inspired Steering Wheel	High Assist Electronic Power Steering with Quick Turn Rack; Race inspired Steer- ing Wheel with Tilt and Telescoping adjustment; Dynamix and Ride Command Push Button Controls
FEATURES	Instrumentation	RIDE COMMAND® T Glove-Touch Display: DYNAMIX 2.0 Visualizer, Built-In GPS, Group ride (cell-based or GPS based), Topographic Mapping, Bluetooth & USB Smartphone Connectivity, AM/FM & Weather Radio, In-Vehicle Communications Capable With Optional Sena Headsets, Rockford Fosgate Premium Audio (Including 2 Tweeters, 2 Front Speakers, and External 400W Amp) Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals. Digital Instrumentation: Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder Light, Gear Indicator, DC Outlet	Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Tempera- ture, Voltmeter, Service Indicator and Codes, Seat Belt Reminder Light, Gear Indicator, DC Outlet	Dual-sweep Analog Dials w/ 4* LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder Light, Gear Indicator, Front and Rear DC Outlet	RIDE COMMAND® 7" Glove-Touch Display: DYNAMIX 2.0 Visualizer, Built-In GPS, Group ride (cell-based or GPS based), Topographic Mapping, Bluetooth & USB Smartphone Connectivity, AM/FT & Weather Radio, In-Vehicle Communications Capable With Optional Sena Headsets, Rockford Fosgate Premium Audio (Including 2 Tweeters, 2 Front Speakers, and External 4000 M amp) Dual-sweep Analog Dials wid "LOD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals. Digital Instrumentation: Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder Light, Gear Indicator, DC Outlet
	Other Standard Features	RIDE COMMAND® , High Output 900w charging system with sealed electrical, Polaris Pulse system, USB Charging, Front Bumper, In-Dash Charge Port, Cut & Sew Seats, Polaris P.A.S.S., Rockford Fosgate Stage 3 Audio.	Adjustable Tilt Steering, Front & Rear LED Accent Lights	High Output 900w charging system with sealed electrical, Polaris Pulse system, In-Dash Charge Port, Polaris P.A.S.S.	RIDE COMMAND®, High Output 900w charging system with sealed electrical, Polaris Pulse system, USB Charging, Front Bumper, In-Dash Charge Port, Cut & Sew Seats, Polaris P.A.S.S., Rockford Fosgate Stage 3 Audio.







#### RZR TURBO R SPORT - 74"

#### RZR TURBO R ULTIMATE - 74"

#### RZR TURBO R 4 ULTIMATE- 74"

	Engine Type	4-Stroke DOHC Twin Cylinder Turbocharged	4-Stroke DOHC Twin Cylinder Turbocharged	4-Stroke DOHC Twin Cylinder Turbocharged
뿔	Displacement	925cc	925cc	925cc
ENGINE	Fuel System / Battery	Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection
	Cooling	Liquid	Liquid	Liquid
AIN	Transmission/ Final Drive	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H
DRIVETRAIN	Drive System	Isolated Xtreme Performance True On-Demand AWD/2WD	Isolated Xtreme Performance True On-Demand AWD/2WD	Isolated Xtreme Performance True On-Demand AWD/2WD
	Engine Braking System / Active Descent Control	Not Equipped / Not Equipped	Not Equipped / Not Equipped	Not Equipped / Not Equipped
NOISN	Front Suspension	Light Weight Boxed Dual A-Arm with 3 piece Stabilizer Bar and 68.6 cm Usable Travel, 56.5 cm Wheel Travel, Unitized Hubs	Light Weight Boxed Dual A-Arm with 3 piece Stabilizer Bar and 68.6 cm Usable Travel, 56.5 cm Wheel Travel, Unitized Hubs	Light Weight Boxed Dual A-Arm with 3 piece Stabilizer Bar and 68.6 cm Usable Travel, 56.5 cm Wheel Travel, Unitized Hubs
SUSPENSION	Rear Suspension	Tubular Trailing Arm with boxed gusseting and Toe Link, High Clearance Radius Rods, and Stabilizer Bar and 71.9cm Usable Travel, 56.9 cm Wheel Travel, Unitized Hubs	Tubular Trailing Arm with boxed gusseting and Toe Link, High Clearance Radius Rods, and Stabilizer Bar and 71.9cm Usable Travel, 56.9 cm Wheel Travel, Unitized Hubs	Tubular Trailing Arm with boxed gusseting and Toe Link, High Clearance Radius Rods, and Stabilizer Bar and 71.9cm Usable Travel, 56.9 cm Wheel Travel, Unitized Hubs
BRAKES	Front/Rear Brakes	4-Wheel Hydraulic Disc with Triple-Bore Front and Dual-Bore Rear Calipers; Aluminum Top Hat Rotor	4-Wheel Hydraulic Disc with Triple-Bore Front and Dual-Bore Rear Calipers; Aluminum Top Hat Rotor	4-Wheel Hydraulic Disc with Triple-Bore Front and Dual-Bore Rear Calipers; Aluminum Top Hat Rotor
BRA	Parking Brake	Park in Transmission	Park in Transmission	Park in Transmission
Βs	Front Tyres	32 x 10-15 Maxxis Rampage Fury; 8-Ply Rated; Wheel Size 15x7	32 x 10-15 Maxxis Rampage Fury; 8-Ply Rated; Wheel Size 15x7	32 x 10-15 Maxxis Rampage Fury; 8-Ply Rated; Wheel Size 15x7
ESA	Rear Tyres	32 x 10-15 Maxxis Rampage Fury; 8-Ply Rated; Wheel Size 15x7	32 x 10-15 Maxxis Rampage Fury; 8-Ply Rated; Wheel Size 15x7	32 x 10-15 Maxxis Rampage Fury; 8-Ply Rated; Wheel Size 15x7
₽×	Wheels	Painted Cast Aluminum Rim with 5-Lug Pattern	Painted Cast Aluminum Rim with 5-Lug Pattern	Painted Cast Aluminum Rim with 5-Lug Pattern
	Wheelbase	244 cm	244 cm	317.5 cm
	Dry Weight	881 kg	913 kg	1,037 kg
	Overall Vehicle Size (L x W x H)	325 x 188 x 189 cm	325 x 188 x 189 cm	340 x 188 x 196 cm
Ĕ	Ground Clearance	40.6 cm	40.6 cm	40.6 cm
A PAC	Seating Capacity	2	2	4
S/C	Fuel Capacity	45.4 L	45.4 L	49.2 L
DIMENSIONS / CAPACITIES	Bed Box Dimensions (L x W x H)	66 x 45 x 29.2 cm	66 x 45 x 29.2 cm	66 x 45 x 29.2 cm
DIME	Front/Rear Rack or Box Capacity	N.A. / 136 kg	N.A. / 136 kg	N.A. / 136 kg
	Payload Capacity	331 kg	331 kg	526 kg
	Hitch Towing Rating	N/A	N/A	N/A
	Hitch Type	Not Equipped	Not Equipped	Not Equipped
	Cargo System/Cab	Lock & Ride®	Lock & Ride®	Lock & Ride® Fold Flat Rear Storage, convertible rear seat storage with integrated tie down points, 70.4 x 134.1 x 49.53 cm
	Lighting	Low/High & Red LED Tail / Brake Lights	Signature White LED, Low/High & Red LED Tail / Brake Lights; Front, Rear, and Interior Accent Lighting	Signature White LED, Low/High & Red LED Tail / Brake Lights; Front, Rear, and Interior Accent Lighting
	Electronic Power Steering	Rack Mounted High Assist Electronic Power Steering with Quick Turn Rack; Race Inspired Steering Wheel with Tilt Adjustment	Rack Mounted High Assist Electronic Power Steering with Ouick Turn Rack; Race Inspired Steering Wheel with Tilt and Tele- scoping Adjustment; DYNAMIX DV with Integrated EPS Modes and Ride Command Push Button Controls	Rack Mounted High Assist Electronic Power Steering with Quick Turn Rack; Race Inspired Steering Wheel with Tilt and Telescoping Adjustment: DYNAMIX DV with Integrated EPS Modes and Ride Command Push Button Controls
FEATURES	Instrumentation	Dual-sweep Analog Dials w/ 4 in LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Bauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder Light, Gear Indicator	RIDE COMMAND™ 7° Glove-Touch Display: Built-In GPS, Mapping, Vehicle-to-Vehicle with "Group Ride, Follow the Leader, & Messaging, Bluetooth & USB Smartphone Connectivity, AM/FM & Weather Radio, In-Vehicle Communications Capable With Optional Sena Headsets, Rockford Fosgate Premium Audio (Including 2 Tweeters, and 2 Front Speakers, and External 400W Amp) Dual-sweep Analog Dials w/ 4 in LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals. Digital Instrumentation: Speedometer, Tachometer, Odometer, Tompeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder Light, Gear Indicator	RIDE COMMAND™ 7" Glove-Touch Display: Built-In GPS, Mapping, Vehicle-to-Vehicle with "Group Ride, Follow the Leader, & Messaging, Bluetooth & USB Smartphone Connectivity, AM/FM & Weather Radio, In-Vehicle Communications Capable With Optional Sena Headsets, Rockford Fosgate Premium Audio (Including 2 Tweeters, and 2 Front Speakers, and External 400W Ampl Dual-sweep Analog Dials w/ 4 in LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals. Digital Instrumentation: Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder Light, Gear Indicator

Other Standard Features

High Output 900w charging system, Polaris Pulse system, In-Dash Vehicle Charge Port, 2 DC Accy ports, Polaris P.A.S.S., Colored Toe Link, Mud and Rock Guards

RIDE COMMAND®, High Output 900W Charging System, Polaris Pulse System, In-Dash Charge Port, 2 front DC Accy ports, Polaris P.A.S.S., Painted Aluminum Roof, Colored Toe Link, Mud and Rock Guards

RIDE COMMAND®, High Output 900W Charging System, Polaris Pulse System, In-Dash Charge Port, 1 front DC Accy ports, 1 rear DC Accy port, Polaris P.A.S.S., Painted Aluminum Roof, Colored Toe Link, Mud and Rock Guards

TYRES AND BRAKES SUSPENSION DRIVETRAIN

DIMENSIONS / CAPACITIES





RZR PRO R ULTIMATE - 74"

Engine Type	4-Stroke DOHC Inline Four Cylinder	4-Stroke DOHC Inline Four Cylinder
Displacement	1997cc	4-Stroke Dunc Hilline Pour Cyllinder
·		
Fuel System / Battery	Electronic Fuel Injection	Electronic Fuel Injection
Cooling Transmission/	Liquid	Liquid
Final Drive	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H
Drive System	Pro Performance True 2WD/4WD/4WD Lock	Pro Performance True 2WD/4WD/4WD Lock
Engine Braking System / Active Descent Control	Not Equipped / Not Equipped	Not Equipped / Not Equipped
Front Suspension	Light Weight Boxed Dual A-Arm with 3 piece Stabilizer Bar and 68.6 cm Usable Travel, 56.5 cm Wheel Travel, Unitized Hubs	Light Weight Boxed Dual A-Arm with 3 piece Stabilizer Bar and 68.6 cm Usable Travel, 56.5 cm Wheel Travel, Unitized Hubs
Rear Suspension	Boxed Trailing Arm with Toe Link, High-Clearance Radius Rods, and 3 piece Stabilizer Bar and 73.7cm Usable Travel, 62.2 cm Wheel Travel, Unitized Hubs	Boxed Trailing Arm with Toe Link, High-Clearance Radius Rods, and 3 piece Stabilizer Bar and 73.7cm Usable Travel, 62.2 cm Wheel Travel, Unitized Hubs
Front/Rear Brakes	4-Wheel Hydraulic Disc with Triple-Bore Front and Dual-Bore Rear Calipers; Aluminum Top Hat Rotor	4-Wheel Hydraulic Disc with Triple-Bore Front and Dual-Bore Rear Calipers; Aluminum Top Hat Rotor
Parking Brake	Park in Transmission	Park in Transmission
Front Tyres	32 x 10-15 Maxxis Rampage Fury; 8-Ply Rated; Wheel Size 15x7	32 x 10-15 Maxxis Rampage Fury; 8-Ply Rated; Wheel Size 15x7
Rear Tyres	32 x 10-15 Maxxis Rampage Fury; 8-Ply Rated; Wheel Size 15x7	32 x 10-15 Maxxis Rampage Fury; 8-Ply Rated; Wheel Size 15x7
Wheels	Painted Cast Aluminum Rim with 5-Lug Pattern	Painted Cast Aluminum Rim with 5-Lug Pattern
Wheelbase	265.4cm	339.1cm
Dry Weight	992 kg	1,125 kg
Overall Vehicle Size (L x W x H)	347 x 188 x 185 cm	420 x 188 x 194 cm
Ground Clearance	40.6 cm	40.6 cm
Seating Capacity	2	4
Fuel Capacity	45.4 L	46.56 L
Bed Box Dimensions (L x W x H)	75 x 60.5 x 20.6 cm	75 x 60.5 x 20.6 cm
Front/Rear Rack or Box Capacity	N.A. / 136 kg	N.A. / 136 kg
Payload Capacity	336 kg	
Hitch Towing Rating		408 kg
	N/A	408 kg N/A
Hitch Type	N/A Not Equipped	,
Hitch Type Cargo System/Cab		N/A
· ·	Not Equipped	N/A  Not Equipped  Lock & Ride™, Convertible Fold Flat rear seat storage with integrated tie downs points, 70.4 x 134.1
Cargo System/Cab	Not Equipped  Lock & Ride® Factory Equipped Cargo Liner  Signature White LED, Low/High & Red LED Tail / Brake Lights; Front, Rear, and Interior	N/A  Not Equipped  Lock & Ride™; Convertible Fold Flat rear seat storage with integrated tie downs points, 70.4 x 134.1 x 49.53 cm Factory Equipped Cargo Liner
Cargo System/Cab Lighting	Not Equipped  Lock & Ride® Factory Equipped Cargo Liner  Signature White LED, Low/High & Red LED Tail / Brake Lights; Front, Rear, and Interior Accent Lighting  Rack Mounted High Assist Electronic Power Steering with Ouick Turn Rack; Race Inspired Steering Wheel with Tilt and Telescoping Adjustment; DYNAMIX DV with	N/A  Not Equipped  Lock & Ride™; Convertible Fold Flat rear seat storage with integrated tie downs points, 70.4 x 134.1 x 49.53 cm Factory Equipped Cargo Liner  Signature White LED, Low/High & Red LED Tail / Brake Lights; Front, Rear, and Interior Accent Lighting  Rack Mounted High Assist Electronic Power Steering with Quick Turn Rack; Race Inspired Steering Wheel with Tilt and Telescoping Adjustment; DYNAMIX DV with Integrated EPS Modes and Ride













## PELARIS Think Outside

www.polarisaustralia.com

/polarisorv\_aus

f / Polaris Australia

f / TeamRZR

Polaris reserves the right to withdraw any product from sale or change specifications and pricing without notice. Confirm model specifications and availability with your Polaris Dealer prior to ordering. The Polaris range is not intended for and may not be registered for on-road use. All competitive comparisons are based on published manufacturer specifications available at December 2022 unless otherwise specified. See other manufacturers for latest specifications. All photography taken with professional riders and drivers. For your safety, always operate Polaris products as instructed in the product manual and on warning labels. Never carry passengers on any product not designed for such use. Preserve your future riding opportunities by showing respect for the environment, local laws and the rights of others. Avoid excessive speeds and be particularly careful on difficult terrain. ©Polaris Sales Australia Pty Ltd ABN 62 088 081 949, Registered Office: 36 Grimes Court, Derrimut, VIC 3028. Printed December 2022.