

6,500W PURE SINE WAVE DIGITAL INVERTER GENERATOR - ELECTRIC, REMOTE & 2-WIRE START



SKU: 123 GI65E

**6,500W Max Power / 2 x 15A IP66
12.5 L Fuel Tank
Recoil / Electric W/Remote FOB**

Features

High-output, pure-sine wave portable power built for backup, off grid solar, worksites and events. The BE GI65E delivers 6500W of pure-sine power that's safe for sensitive electronics. Electric and remote start make life easy, while the included 2-wire start cable integrates with solar/remote systems for hands-off backup and battery charging.

- Pure Sine Wave inverter output (safe for sensitive electronics)
- Electric start – push-button convenience and key FOB
- BE Power APP control for iOS and Android
- Remote/2-wire start ready for solar or remote integration - Cable Included
- On-board battery charger for keeping the generator internal 12 V battery topped up
- Auto Idle (Eco/Smart-throttle) for lower noise and fuel use
- LED panel light & multifunction display (status/runtime info)
- Covered IP66 waterproof outlets + USB adapter (model dependent)
- Parallel-link capable (optional kit)
- Low-oil shutdown with magnet dipstick
- Carburettor with easy drain to purge stale fuel
- NGK spark plug for reliable starts
- Copper PM alternator for stable output
- UV8-resistant body with rain cover included
- Robust, service-friendly design with practical carry points
- Engine oil included (first fill)*

Specifications

- **Control Output:** 6,000
- **Max Output:** 6,500
- **Industry Rating:** 8.1 kVA
- **Frequency:** 50 Hz



6,500W PURE SINE WAVE DIGITAL INVERTER GENERATOR - ELECTRIC, REMOTE & 2-WIRE START



- **Voltage:** 240 V
 - **Outlets:** 2 x 15A IP66
 - **12 V Outlets:** 1 x DC 12 V 8A
 - **Max Amps:** 25 A
 - **Engine:** 312 CC
 - **Max Engine Speed:** 3,600 RPM
 - **Noise Level @ 7m:** 68 dBA
 - **Fuel Tank:** 12.5 L
 - **Fuel Type:** Unleaded Gasoline
 - **Starting:** Recoil/Electric W/Remote FOB
 - **APP Control:** YES
 - **2-Wire Start:** YES
 - **Wheel Kit:** YES
 - **Neutral Configuration:** Floating
 - **Gross Weight:** 59 kg
 - **Product Dimensions:** L 62 cm x W 49.8 cm x H 55.3 cm
 - **Packaging Dimensions:** L 65 cm x W 54 cm x H 58.3 cm
-

